

DATA SHEET



WIDE DYNAMIC RANGE & DAY/NIGHT HD IP CAMERAS

The CamVu720 WDR Series are high definition IP Cameras offering HD720 image streams in a choice of compression formats. With advanced features such as ICR (Integrated Camera Recording), analytics support and direct configuration from associated Video Servers, the CamVu720 WDR Series contains a powerful suite of enterprise-scale capabilities. The CamVu720 WDR Series is also designed for Dedicated Micros next generation of video surveillance - Closed IPTV.

HIGH DEFINITION STREAMING & RECORDING

The CamVu720 WDR Series provides high definition image streams up to HD720. The powerful suite of streaming features ensure flexibility in remote viewing of the camera whilst on-board storage and supported transmission protocols such as AoE provide a wealth of local and remote recording options..

AnalyticsCapable

As part of our growing range of **AnalyticsCapable** products, the CamVu720 WDR Series is able to contain the latest analytics solutions from Dedicated Micros including Object Left/Removed Detection Tripwire and Counting Tripwire, all locally hosted on the camera.

NETVU CONNECTED

With NetVu Connected products users can seamlessly integrate Video Servers, Cameras & Domes, Management Systems, mobile viewing devices and video walls together without the costly impact of significant integration time. A shared user interface helps minimise operator training whilst powerful features such as Direct configuration of PTZ Cameras and Domes from connected DVRs helps reduce installation time providing benefits to both end user and installer/integrator.

The incredible flexibility of Dedicated Micros NetVu Connected platform enables multi-environment security installations to be achieved with ease. Integration of Fixed and Mobile DVRs and Video Servers alongside products such as FireVu (for Video Smoke Detection) enable large scale solutions with several application requirements to be designed and built with ease.

MULTIPLE, SIMULTANEOUS VIDEO STREAMS

Dedicated Micros' unique Visual Signal Processor (ViSP) allows the CamVu720 WDR Series to transmit multiple simultaneous MPEG-4, H.264 and/ or JPEG images to any number of associated NetVu Connected devices for image viewing. Each stream can be tailored to suit the viewer's bandwidth requirements.

CLOSED IPTV

Dedicated Micros' award winning Closed IPTV solution combines open standard IP protocols with patent pending innovation to provide simple to install, safe and secure IP video solutions across new or existing networks.

Automatically allocating IP addresses to IP cameras by physical port, a Closed IPTV system is completely deterministic, creating firewalls and monitoring point-to-point IP connections so they cannot be hacked or intercepted. Critical to the security of a Closed IPTV system is the unique implementation of Trusted Endpoint technology; a secret signature, applied at lock down, enables endpoint devices such as IP cameras to be secure, immediately triggering a security alert should any interference be detected.

This ground breaking solution provides a very simple and secure answer to IP video, meaning that no prior knowledge of IP networking is required. Sophisticated and Dependable network security can be achieved with a single click.

DM/CV/B720WNM	Box Camera, Day/Night, Wide Dynamic Range
DM/CV/D720WCM	Mini Dome, Colour Only, Wide Dynamic Range
DM/CV/V720WNM	Vandal Dome, Day/Night, Wide Dynamic Range

FEATURES

- High definition IP Camera - up to HD720 resolution
- Available in static camera, internal mini-dome or Vandal Resistant Mini-dome options
- Integrated Camera Recording and full enterprise video server within camera
- Can form part of a Closed IPTV system
- Transmission of multiple, simultaneous video streams in MPEG-4, H.264 and JPEG format enables multiple users to view video streams at the settings they require
- **AnalyticsCapable** - enables analytics solutions to be deployed on your CCTV system
- Works with any DM Video Server that supports IP Streaming & Recording
- **MultiMode Recording** - Dynamically-switchable resolution, record-rate & compression (MPEG-4/H.264/JPEG) settings
- Web server for remote configuration of camera features
- Power over Ethernet (PoE) / 12-24Vdc & 24Vac power options
- Local analogue test monitor output for use when positioning and adjusting the camera's field of view and focus
- DM/CV/B720WNM can be used externally in a compatible housing such as a DM/2010
- **TransCoding** - High quality recording and simultaneous video transmission using MPEG4, JPEG or H.264 for playback
- Uses the latest Chipwrights ViSP to minimise power consumption and heat build up



TECHNICAL SPECIFICATION

CAMERA SPECIFICATION

IMAGE SENSOR

1 / 2.7" CMOS progressive scan

VIDEO PROCESSOR

SoC DSP (CW5631)

MINIMUM ILLUMINATION

0.1 lux at 25fps

LENS

CV/B720WNM: C/CS with back focus adjustment ring. Direct drive DC iris via 4-pin square type socket on the side of the camera. Most 1/3" lenses can be used. Integrated physical IR cut filter - software controlled

CV/D720WCM: Integrated 3-8mm Varifocal with DC iris, F1.3. Aspherical glass with IR corrective coating

CV/V720WNM: Integrated 3-8mm Varifocal with DC iris, F1.3. Aspherical glass with IR corrective coating. Physical IR cut filter - software controlled

VIDEO SPECIFICATION

COMPRESSION

JPEG, H.264 and MPEG-4.

MAXIMUM OUTPUT RESOLUTION

720p (16:9 Ratio)

MAXIMUM IMAGE RATE

Maximum 30pps @ HD720 (single connection to camera)
1280x720 (16:9, 1MP) - multistream

IMAGE STREAMING

Multiple, simultaneous, individual video streams in any supported compression format, bit rate or resolution can be sent to any connected user

TransCoding

Transmit multiple simultaneous MPEG-4, H.264 and/or MJPEG recorded image streams to any number of associated NetVu Connected devices for image viewing. Each stream can be tailored to suit bandwidth requirements. Resolution and format can be dynamically changed without the need to stop and then restart the stream. This operation is carried out independently of high resolution recordings.

COMPOSITE VIDEO OUTPUT

(PAL / NTSC) live display, initially operational for 10 minutes (user configurable) to enable camera focusing / configuration. Video output can also be used as part of a media display or emergency messaging capability.

INTEGRATED CAMERA RECORDING (ICR)

ICR combines recording capability and a full enterprise video server within the camera. Record camera footage at the unit as well as any associated Video Server. An integrated Micro SD expansion port provides local recording capability whilst ATA over Ethernet (AoE) protocol provides highly-secure point-to-point transfer of video files to separate, remote, storage devices for backup and longterm archiving. Enables a tiered storage architecture that ensures no single point of failure.

IMAGE CONTROL

Camera Title, Lens Select, Electronic Iris, Exposure Level, Flip/Mirror Video, Sharpness Control

NETWORK & CONFIGURATION SPECIFICATION

NETWORK SUPPORT

DCCP, DHCP, HTTP, HTTPS, IPv4, SMTP, Bonjour, ICMP, DNS, NTP, TCP, UDP, ICMP, DHCP, ARP, RTP, Telnet, FTP, AoE, SNMP, ZeroConf

WEB PAGE CONFIGURATION

Simple Web page configuration will allow the following functions to be configured: Camera setup, Manual update of viewing profiles, Network and Alarm settings (CV/V720WNM includes Audio Settings)

DIRECT CAMERA CONFIGURATION

Directly configure from the associated NetVu Connected Video Server. In addition, when used within a Closed IPTV system, default settings (such as streaming rate, resolution, aspect ratio, telemetry, lens configuration etc.) can be automatically assigned to the camera

INTEGRATION SPECIFICATION

APPLICATION SUPPORT

Browser: IE 5.5 / Firefox 2.0 and above
Developer: Java via Dedicated Micros SDK

NETVU OBSERVER - SEAMLESS VIDEO MANAGEMENT

Dedicated Micros NetVu ObserVer video management software allows seamless viewing and control of live and recorded images from any NetVu Connected product (IP or analogue) in a single interface. The ability to view multiple sites simultaneously makes management of any security installation efficient. The inclusion of RVRC (ARC) features such as EDP, event characterisation and report generation make NetVu ObserVer ideal for remote monitoring of multiple sites. (Supplied with Product, Apple Mac Version Available)

ALARMS & RELAYS

Video Motion Detection (VMD) & Activity Detection, Zoned alarms based on multiple inputs. On alarm actions include: Alarm Reporting, Record Profile change, Email, Relay Closure (Relay closure on models with relay outputs only)

CV/V720WNM: 2 physical alarm inputs & 1 physical relay output.

AUDIO

CV/V720WNM: 1x audio input (mono) – 3.5mm jack, 47kΩ input impedance, 1x audio output (mono) – 3.5mm jack, 47kΩ input impedance

GENERAL SPECIFICATION

ENCLOSURE

CV/B720WNM: Zintec case, Cast Zinc lens mount, V0 ABS trim

CV/D720WCM: Grey ABS. Clear polycarbonate bubble

CV/V720WNM: IP66 Die cast aluminium LM25 Base, Lexan Polycarbonate Bubble

CONNECTIONS

Ethernet: 10/100 BaseT RJ45 Connector PoE

Storage: Micro SD slot for recording. Supplied with 2GB class 4 card.

CV/B720WNM: Secondary Micro SD slot for recording

Power: Terminal Block

CV/V720WNM: Terminal Block for Alarms & Relays

MOUNTING OPTIONS

CV/B720WNM: 1/4" 20 UNC mounts on top and bottom

CV/D720WCM: Ceiling, Surface (via provided fixings), 3-axis GyroView set up

CV/V720WNM: Surface (via provided fixings), 3-axis GyroView set up

MEASUREMENTS

CV/B720WNM: 123 (L) x 60 (H) x 60 (W) (mm)

CV/D720WCM: 120 (L) x 120 (W) x 110 (H) (mm)

CV/V720WNM: 148 (L) x 148 (W) x 104 (H) (mm)

WEIGHT

CV/B720WNM: 0.4kg (14oz) without lens

CV/D720WCM: 0.3kg (10.5oz)

CV/V720WNM: 1.18kg (41.6oz)

POWER

CV/B720WNM: 12Vdc-24Vac/PoE, Consumption: 4.5W

CV/D720WCM: PoE only, Consumption: 4.5W

CV/V720WNM: 12Vdc/PoE, Consumption: 4.5W

POWER OVER ETHERNET

IEEE 802.3-2008. End span and bridging injectors supported. Supplied with a PoE injector to allow power to be applied to the connecting Ethernet cable without the need for a PoE enabled network switch. This allows 48V power (supplied separately) to be provided down the line to the camera on the same cable that is used for data transmission.

ENVIRONMENTAL

Operating Temperature (CV/B720WNM / CV/D720WCM): -10° to +50°C (14° to 122°F), Operating Temperature (CV/V720WNM): -30° to +50°C (-22° to 122°F)

Operating Humidity: 20% to 80% relative humidity, non condensing

Storage Temperature: -10° to +70°C (14° to 158°F)

Storage Humidity: 20% to 90% relative humidity, non condensing

WARRANTY

2 Years

Model Code	Description
DM/CV/B720WNM	CamVu 720p WDR DN IP Camera PoE/12vDC/24vAC
DM/CV/D720WCM	CamVu 720p WDR IP Dome PoE
DM/CV/V720WNM	CamVu 720p WDR DN IP VR Dome PoE/12vDC

Add N at end of pin code to enable default output and configuration to be applied for US market



To find your nearest Dedicated Micros office, please visit

www.dedicatedmicros.com

Head Office: Dedicated Micros UK, 1200 Daresbury Park, Daresbury, Warrington, WA4 4HS Tel: +44 (0) 845 600 9500 Fax: +44 (0) 845 600 9504 Email: customerservices@dmicros.com

Note: Image used is for illustrative purposes only - DM/CV/B720WNM cameras are not supplied with lens. The manufacturer reserves the right to change the specification without notice. All trademarks are courtesy of registered owners. DV-IP is trademark of AD Holdings plc. The DM logo is a trademark of Dedicated Microcomputers Group Ltd. NetVu Connected is a trademark of the AD group. © Copyright AD Group June 2012

MKT-CMVU720WDR-D-001E

