

## **PROCUREMENT SPECIFICATION**

### **MODEL TT212 MANUAL CABLE CRASH BEAM BOLLARD MOUNTED**

#### **1.0 SCOPE**

This specification defines the procurement of a CABLE CRASH BEAM BARRIER, Model TT212, consisting of a hinged rigid wire rope crash beam, counter weights, locking pin with padlock hasp, mounting hardware, cast in place supports, and options as defined herein.

#### **2.0 SYSTEM CONFIGURATION**

- 2.1 **Barrier Construction.** Barrier shall be an above grade assembly containing a hinged rigid wire rope crash beam counterbalanced for easy operation. When in the down position the beam shall present a formidable obstacle to approaching vehicles. Upon impact, the force shall first be absorbed by the rope beam assembly and then transmitted to the foundation bollards of the unit.
- 2.2 **Barrier Height.** Height of the Barrier shall nominally be 30 inches (762 mm) as measured from the roadway surface to the center line of the crash beam. Height can be varied to suit security threat analysis.
- 2.3 **Barrier Length.** Barrier length shall be 126 inches (3,2 M) as measured inside to inside (clear opening) of the bollard supports (Barrier can be optionally specified with lengths of 72 inches [1,8 M] to a maximum length of 288 inches [7,3 M]).
- 2.4 **Finish.** The foundation base of the Barrier shall be asphalt emulsion coated for corrosion protection. Barrier top surface shall have a rust inhibiting painted surface. The wire rope shall be galvanized. The wire rope supporting tube shall be provided with yellow/black safety tape (alternating red/white safety tape).

#### **3.0 OPERATION**

- 3.1 **Manual Operation.** The Barrier shall be effectively counterbalanced to be capable of being raised or lowered with minimal manual effort.

#### **4.0 PERFORMANCE**

- 4.1 Experience. Barrier and auxiliary equipment shall be of a proven design. Manufacturer shall have 15 years documented experience with similar vehicle Barriers.
- 4.2 Qualification Tests. Barrier design shall be successfully passed actual crash tests performed by an independent agency.
- 4.2.1 Barrier shall have a performance evaluation per US Navy TM-56-86-05 of 1/L3.0.
- 4.3 Stopping Capacity
  - 4.3.1 Normal Operation. Barrier shall provide excellent security and positive control of normal traffic in both directions by providing an almost insurmountable obstacle to non-armored or non-tracked vehicles. The Barrier system shall be designed to stop a vehicle attacking from either direction when the vehicle is within the weight and velocity characteristics as defined in paragraph 4.3.1.1. Damage to the Barrier system is probable at these levels.

4.3.1.1 The Barrier shall be capable of stopping a vehicle(s) weighing:

6,000 pounds at 40 mph (26,7 KN at 64 kph)  
10,000 pounds at 27 mph (44,4 KN at 43 kph)

#### **5.0 BEAM LOCKING METHOD**

- 5.1 Manual Locking Pin. The Barrier shall be provided with a locking pin with padlock hasp for securing the Barrier in the down position. The padlock will be furnished by others.

#### **6.0 QUALITY ASSURANCE PROVISIONS**

- 6.1 Testing. Upon completion, the Barrier system will be fully tested in the manufacturer's shop. The following checks shall be made:
  - 6.1.1 Identification. A nameplate with manufacturer's name, model number, serial number and year built shall be located at the hinged end structure.
  - 6.1.2 Workmanship. The Barrier shall have a neat and workmanlike appearance.
  - 6.1.3 Dimensions. Principle dimensions shall be checked against drawings and ordering information.
  - 6.1.4 Finish. Coatings shall be checked against ordering information and shall be workmanlike in appearance.

## **7.0 PREPARATION FOR SHIPMENT**

- 7.1 The Barrier system shall be crated or mounted on skids as necessary to prevent damage from handling. The shipping container(s) shall be of sufficient structural integrity to enable the assembly to be lifted and transported by overhead crane or forklift without failure.

## **8.0 DISCLAIMER**

Please note - careful consideration must be devoted to the selection, placement and design of Cable Crash Beam Barrier installation. Just as in the case of any Barricade system, perimeter security device or security gate that blocks a roadway or drive, care must be taken to ensure that approaching vehicle as well as pedestrians are fully aware of the Barriers and their operation. Proper illumination, clearly worded warning signs, auxiliary devices such as semaphore gates, stop-go signal lights, audible warning devices, speed bumps, flashing lights, beacons, etc. should be considered. Delta has information available on many such auxiliary safety equipment not specifically listed herein. It is strongly recommended that an architect and or a traffic and or safety engineer be consulted prior to installation of a Barricade system. Delta will offer all possible assistance in designing the operating equipment, controls and the overall system but we are not qualified nor do we purport to offer either traffic or safety engineering information.

## **9.0 PROCUREMENT SOURCE**

The **Model TT212** Cable Crash Beam Barrier System shall be purchased from:

### **DELTA SCIENTIFIC CORPORATION**

40355 Delta Lane  
Palmdale, California, 93551, USA  
Phone (661)575-1100  
FAX (661)575-1109  
email [info@deltascientific.com](mailto:info@deltascientific.com)  
[www.deltascientific.com](http://www.deltascientific.com)