Edgeport/1






Bump-in-the-Cable Solution for Serial Port Expansion

he Edgeport/1 USB-to-serial converter is the newest member of the Edgeport family of enterprise Universal Serial Port (USB) connectivity solutions. One-sixth the size of our Edgeport/2, this single port solution is merely a bump in the cable, yet it has the same reliability, performance and operating system support that Edgeport users have come to expect. Simply plug the Edgeport/1 into the USB port of a desktop PC, laptop, or thin client and gain one high-speed RS-232 DB-9 serial port. Attaching PDAs, printers, bar code scanners, and other peripheral devices has never been easier! The Edgeport/1 is perfect for



mission-critical applications such as point-of-sale and mobile computing in which space is limited and flexible I/O expansion is required.

Point-of-Sale



Proven Performance for the Enterprise User

- Same reliability, performance, and no-hassle installation of our flagship Edgeport USB expansion boxes
- Operating system support for Windows®95, 2000, NT 4.0, XP, and more
- Lower cost per port than serial boards; external solution allows use of a smaller, lower cost PC
- Small form factor is easy to transport and takes up virtually no space weighs less than 2 oz / 57 g
- Jack screws keep your serial device securely in place
- Eliminates long cables between the peripheral device and computer
- Bulk pricing available for large installations and OEM opportunities



PART#

301-1001-11

EDGEPORT/1 MODELS NAME DESCRIPTION Edgeport/1 1 RS-232 serial DB-9

EDGEPORT/1 BULK PACKS		
NAME	DESCRIPTION	PART#
25-Unit Bulk Pack	25 Edgeport/1 units	301-1001-21
100-Unit Bulk Pack	100 Edgeport/1units	301-1001-22

Each Edgeport/1 ships with detachable 1 meter USB cable.

Bulk Packs include one copy of software, documentation, and limited use software and documentation reproduction license.









To view our entire line of USB solutions visit our website at www.ionetworks.com

Edgeport/1 Technical Features and Specifications

FEATURES

- Baud rate: Up to 230Kbps
- Configurable COM port assignment
- Unit maintains COM port assignments across reboots
- USB 1.0, 1.1 and 2.0 compliant
- Plug-and-play compliant; hot-swappable
- Full hardware and software flow control support
- UART: 128-byte buffer per direction
- User diagnostics
- Easy configuration
- Status reporting
- No additional IRQ or I/O port requirements

SYSTEM REQUIREMENTS

- Windows 95 (OSR2), 98, SE, 2000, Me, CE,
 XP, XP Embedded, NT 4.0, NT Embedded; Linux
- 1 USB type A (downstream) port

POWER REQUIREMENTS

 No external power supply needed (USB-powered)

ENVIRONMENTAL REQUIREMENTS

- Ambient temperature: 32°-149°F (0°-65°C)
- Relative humidity: 0-95% non-condensing

CERTIFICATION AND SAFETY

- FCC Part 15 Class B
- CE Certified
- EN55022, Class B
- EN55024
- EN60950
- UL 1950
- CSA No. 950

Inside Out Networks

7004 Bee Caves Road Building 3, Suite 200 Austin, Texas 78746

(512) 306-0600 (512) 306-0694 Fax (877) 912-3444 Digi toll-free

Digi Europe: +49-231-9747-0; Digi Hong Kong: +852-2833-1008 Digi Web: www.digi.com; Digi e-mail: info@digi.com





©2001 Inside Out Networks. Inside Out Networks and the Inside Out Networks logo are trademarks of Inside Out Networks. Digi, Digi International, the Digi logo, and Edgeport are either trademarks or registered trademarks of Digi International, Inc. All other trademarks or registered trademarks are the property of their respective owners.