



DD2100 - Indoor B&W Dome Camera

Features

- 1/3" B&W CCD
- 380 TV Lines of Resolution
- 0.5 Lux at F2.0
- 360° adjustable Viewing Direction
- Polycarbonate Dome

An easy to install, compact Standard Resolution B&W dome. The unit has a resolution of 380 TV lines and a minimum illumination of less than 0.5 Lux at F2.0 The compact design is suitable for modern interior places such as hotels, theaters, restaurants, airports, department stores, and office buildings.

Specifications

Image Sensor	1/3" Interline transfer type B&W CCD
Effective Pixels (CCIR)	500H x 582V (290K)
Scanning System (CCIR)	625 Lines 2:1 Interlace
Scanning Frequency (CCIR)	15.625KHz (H), 50Hz (V)
Resolution	380 TV-Lines
Shutter Speed (CCIR)	1/50 ~ 1/100,000 sec.
S/N Ratio	More than 48dB (AGC off)
Sync. System	Internal
Min. Illumination	0.5 LUX (F2.0)
Gain Control	Automatic
Video Output	1.0 Vp-p (75Ω load)
Lens	Fixed (3.6mm)
Power Supply	DC12V ± 10%
Power Consumption	<100mA (DC12V)
Operating Temp	-10 to +45 C / 14 to 113F
Operating Humidity	90% RH Max.
Diameter	125mm