# WS4949 Two-Button Wireless Key



#### **Product Features:**

- Cost effective
- ► Two-button, three-channel wireless key
- Activation via two large, scratch-resistant buttons
- Attractive, compact design
- Full three-second delay on panic function
- ► Integrated LED to indicate signal transmission
- Reliable 433MHz technology
- Long-life lithium batteries included
- FCC/IC approved



## **WS4949**

The WS4949 two-button wireless key adds wireless convenience and value to any DSC security system by providing users with a competitively priced wireless solution that includes a number of features and benefits. The WS4949 provides users with a sense of control over their security system and the added confidence that comes with portable personal protection within the home. Compact and user-friendly, the WS4949 features two scratch-resistant buttons that when activated perform either away arming or disarm functions. When the two buttons are pressed simultaneously the panic function is activated.

#### **False Alarm Reduction**

False alarm reduction has resulted in the introduction of activation delays that require users to press and hold a button for a period of time before its function is initiated. To activate the away arming/disarm functions of the WS4949, press and hold the appropriate button until the one-second activation delay expires. The WS4949 incorporates a full, three-second activation delay on its panic function to help reduce false alarms. To activate it, both buttons need to be pressed simultaneously.

#### **Visual Confirmation**

A red LED indicator, located between the two buttons on the WS4949, flashes to indicate that a transmission has been sent to the security system.

#### Value Added

Distributed by:

The WS4949 uses reliable 433MHz wireless technology, long-life lithium batteries and is compatible with all of DSC's current wireless receivers.

<b>Ordering Information:</b>	
WS4949	2-Button Wireless Key



## **Compatibility**

The WS4949 is compatible with the following receivers:

MAXSYS® Wireless Receiver PC4164-433

PowerSeries™ Wireless Receiver Zone Expansion Module PC5132-433

Wireless Receiver RF5108-433

Fixed-Message LCD Keypad with Integrated Wireless Receiver RF5501-433

Envoy™ LCD Self-Contained Wireless Security System NT9005

## **Specifications**

Dimensions	2 1/4" x1 1/4" x 7/16"
	(57mm x 32mm x 13mm)
Weight	0.6oz
	(18g)
Operating Environment	32° to 120°F
	(0° to 49°C)
Relative Humidity	5% to 93%

©2004 2004·08