

<b>1725L/1727L</b>	<b>Desktop</b>	
<b>3000 Series</b> <b>17" LCD Touchmonitor</b>		

**SPECIFICATIONS**

<b>Model</b>	1725L/1727L	
<b>Case/Bezel color</b>	Dark gray/Beige	
<b>Display type</b>	Active matrix TFT LCD	
<b>Display size</b>	17.0" diagonal	
<b>Useful screen area</b>	Horizontal	13.3" (338 mm)
	Vertical	10.6" (270 mm)
<b>Monitor dimensions</b>	Width	17.09" (434 mm)
	Height (including base)	16.93" (430 mm)
	Depth (including base)	9.37" (238 mm)
<b>Dimensional drawing number</b>	MS500231 (available at <a href="http://www.elotouch.com">www.elotouch.com</a> )	
<b>Optimal (native) resolution</b>	1280 x 1024 at 75 Hz	
<b>Other supported resolutions</b>	1024 x 768 at 60, 70, or 75 Hz; 832 x 624 at 75 Hz (Mac); 800 x 600 at 56, 60, 72, or 75 Hz; 640 x 480 at 66 Hz (Mac); 640 x 480 at 60, 72, or 75 Hz; 720 x 400 at 70 Hz	
<b>Colors</b>	16.7 million (24-bit)	
<b>Brightness</b>	LCDpanel	250 cd/m <sup>2</sup>
	LCDpanel with touchscreen	AccuTouch: 200 cd/m <sup>2</sup> (typical); IntelliTouch: 230 cd/m <sup>2</sup> (typical)
<b>Viewing angle (from center)</b>	Horizontal (left/right)	±80° or 160° (CR = 5)
	Vertical (up/down)	55°/80° or 135° total (CR = 5)
<b>Contrast ratio</b>	400:1	
<b>Input video format</b>	Analog (no proprietary video card needed) or Digital Video Input (DVI-D)	
<b>Input video signal connector</b>	Mini D-Sub 15-Pin (female) or Digital 24-Pin Input	
<b>Scanning frequency</b>	Horizontal 31.5–80 kHz; vertical 56–75 Hz	
<b>Video bandwidth</b>	135 MHz	
<b>Power supply</b>	External power supply, 100–240 VAC, 50–60 Hz, monitor input power 19 V at 2.65 A	
<b>Power dissipation</b>	50 W max.	
<b>Temperature</b>	Operating 0°C to 40°C; storage –20°C to 60°C	
<b>Humidity</b>	Operating 20% to 80%; storage 10% to 90%; noncondensing	
<b>Weight (approx.)</b>	Typical 21.6 lbs (9.8 kg); shipping 30.6 lbs (13.9 kg)	
<b>Warranty</b>	Monitor	3 years
	Touch technology	5 years AccuTouch touchscreen; 10 years IntelliTouch touchscreen
	Backlight lamp life	30,000 hours
<b>Other features</b>	Digital on-screen display (OSD); two built-in 2 W speakers; removable base; sealing; VESA mounting; 100 mm or 75 mm VESA Mounting; wall mountable when installed by qualified personnel; User's controls: side: auto, enter, ±, menu, power; OSD: contrast, brightness, H/V position, color, temperature, clock, phase, recall, OSD time, language (English, German, Spanish, Japanese, French); OSD disable/enable; power, volume, and/or OSD menu	

**ORDERING INFORMATION**

			<b>Touch Technology</b>	<b>Touch Interface</b>	<b>Surface Treatment</b>	<b>Elo Part Number</b>	<b>Agency Approvals</b>
Dark gray	AccuTouch	Serial	Antiglare	954174-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		
Dark gray	AccuTouch	USB	Antiglare	069914-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		
Dark gray	IntelliTouch	Serial	Antiglare	D00405-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		
Dark gray	IntelliTouch	USB	Antiglare	442072-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		
Beige	AccuTouch	Serial	Antiglare	482392-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		
Beige	AccuTouch	USB	Antiglare	227258-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		
Beige	IntelliTouch	Serial	Antiglare	D33055-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		
Beige	IntelliTouch	USB	Antiglare	869890-000	UL, cUL, FCC, IC, CE, TÜV-GS, VCCI, C-Tick		

- Users should independently evaluate the suitability of the product for their application.
- All prices, models, and availability subject to change without notice.

- Stock quantities may be limited. Larger quantities are available within one week.
- For Product Agency Certifications refer to our Web site.