



## BLR-3004/1.5DV

Article-No.: 72965

Digital Video Recorder (4 Channels), H.264, 1.5TB, 100fps, 704x576, DVD, 230V

### Mainfeatures

4 video inputs / DVI&composite outputs  
PAL/NTSC, Quadplex operation  
Recording speed: 100 ips. max.  
1500Gbyte SATA HDD (no HDD extention possible)  
Secondary storage / Archiving via USB and DV-RW  
RS-485 ports (telemetry control)

Alarm inputs and outputs  
H.264 video compression  
Video resolution 704x576 px. max.  
Recording modes: permanent, time, alarm, panic  
Multiple language on-screen menu control  
Ethernet connectivity

### Specifications

Series	eneo BLR
Operation mode	Quadplex
Operation Mode	backup, playback, record, network
Video standard	PAL/NTSC
Video inputs (amount)	4
Video inputs	1Vp-p, (C)VBS, 75ohms, BNC
Main video outputs	DVI, composite (CVBS)
Video outputs	1Vp-p, 75ohms, BNC
Spot monitor	1x composite (CVBS)
IP channels	-
Audio inputs	-
Alarm inputs	4x TTL, programmable as NC/NO
Motion detector	18x22 (396) grid, sensitivity levels: 10
Covert camera mode	available
Alarm triggers	video loss, motion detection, contact, change of configuration, disk error, acoustic
Alarm outputs	1x NO/NC contact

## Specifications (continued)

Alarm notification	e-mail notification
Event logs	yes
Max. recording resolution	704 x 576
Compression standard	H.264
Max. recording rate	100 B./Sek.
Max. recording rate	@ 704 x 288
Recording speed	50 fps @ 704 x 576, 100 fps @ 352 x 288
Digital storage media	SATA HDD, Built-in DVD-RW
Harddisk capacity (internal)	1,5 TB
Max. harddisk capacity (internal)	4 TB
Recording	per channel, permanent, timer, movement, contact, panic
Digital signature	watermark
Pre-alarm recording	up to 5sec.
Post-alarm recording	up to 180sec.
Playback	full screen, 4 channel split, split sequence
Zoom function	up to 8x (full screen mode/live operation)
Search function	date/time, event, calendar
Intergrated writer	DVD
Secondary Storage	USB-port external HDD, via DVD-RW
Control units (external)	mouse
Remote access	Microsoft Internet Explorer, Mozilla Firefox, Opera, Safari (MAC), iPhone, Android, BlackBerry
Mobile access	iPhone, Blackberry, Android OS
Time synchronization	NTP
Menu languages	German, English, French, Spanish, Turkish, Russian, Polish, Portugese, Dutch, Greek, Korean, Japanese, Italian, Chinese, Persian, Bulgarian, Brasilian
Network	10/100 Base-Tx, RJ45
Network protocols	IPv4
Transmission rate (Network)	TCP/IP, DHCP, DDNS
Firmware update	8 levels (56kbit/s ~ 8Mbit/s)
Interfaces external storage	USB Flash drive
Serial interfaces	USB
Serial interfaces	RS-485
Serial interfaces protocols	(PTZ control)
Password protection	Fastrax IIE, Pelco D, Pelco P
Operation system	administrator, manager and users
Supply voltage	Linux
Power consumption	12VDC
Temperature range (operation)	40W
Housing	0°C ~ +40°C
Dimensions (HxWxD)	steel metal with plastic front, desktop design
Weight	67x360x390mm
Parts supplied	4.2kg
Certificates	IR remote controller, installation CD, power cord, PSU 100~240VAC, DVI / VGA adapter, remote viewer software
	CE

## Optional Accessories

<i>Image</i>	<i>Artikel-Nr. / Typ</i>	<i>Description</i>
	DVR-MOUSE	USB Mouse for Recorder Series DTR, DPR, BLR and DLR3/4 - PS/2, USB

Your partner for eneo products:

