



DLR-1004/500V

Article-No.: 72977

Digital Video Recorder (4 Channels), H.264, 720x576, 100fps, 500GB

Mainfeatures

Quadplex operation

Resolution: 704x576 px. max.

VGA and composite output

Secondary storage / Archiving via USB 2.0

Storage capacity: 500GByte

IR remote control and mouse control

H.264 video compression standard

Recording speed: 100 ips max.

Network connectivity (10/100Base-T Ethernet)

Live picture & playback zoom (2x)

Integral motion detector

Webguard remote software





Specifications

Series	eneo DLR
Operation mode	Quadplex
Operation Mode	playback, record, network, backup
Video standard	PAL / NTSC (auto selection)
Video inputs (amount)	4
Video inputs	1Vp-p, (C)VBS, 75ohms, BNC
Main video outputs	VGA, CVBS
Video outputs	1Vp-p, 75ohms, BNC
Spot monitor	no
Audio inputs	-
Alarm inputs	no
Motion detector	integrated
Alarm triggers	video loss, motion detection
Alarm outputs	no
Alarm notification	e-mail, remote software
Event logs	up to 5000

Specifications (continued)

Max. recording resolution	704 x 576
Compression standard	H.264
Max. recording rate	100 B./Sek.
Max. recording rate	@ 352 x 288
Recording speed	100 ips at 352x288 Px., 100 ips at 704x288 Px., 50 ips at 704x576 Px. (PAL)
Digital storage media	one SATA hard disk, not extensible
Harddisk capacity (internal)	500 GB
Max. harddisk capacity (internal)	2 TB
Recording	permanent, movement, timer, event
Digital signature	watermark
Pre-alarm recording	up to 30sec.
Post-alarm recording	up to 60sec.
Playback	full screen, 4 channel split
Patrol mode	yes
Playback speed	100 ips. at CIF (352x288 Px.), 50 ips. at 2CIF (704x288 Px.), 25 ips. at 4CIF (704x576 Px.) / PAL
Zoom function	in full screen mode (live and playback operation)
Search function	via time, date and event
Integrated writer	no
Secondary Storage	via USB 2.0: HDD, Flash drive, Network Data Export: Clip Player, AVI, JPG, BMP
Control units (external)	mouse
Remote access	remote software, Microsoft Internet Explorer
Mobile access	iPhone, PDA
Menu languages	German, English, French, Italian, Spanish, Polish, Hungarian, Czech, Danish, Dutch, Russian
Network	10/100 Base-Tx, RJ45
Network protocols	IPv4
Firmware update	TCP/IP, DHCP, SMTP
Interfaces external storage	via remote software, USB Flash drive
Serial interfaces	USB
Password protection	no
Key locking	yes
Operation system	no
Supply voltage	Embedded Linux
Power consumption	120 / 240VAC via external PSU
Temperature range (operation)	15W
Housing	+5°C ~ +40°C
Colour	metal with plastic caps
Dimensions (HxWxD)	black
Weight	45x260x185mm
Parts supplied	1.35kg
Remarks	PSU 100~240VAC, IR remote controller, manuals, remote viewer software
Certificates	Very low noise (without fan)
	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	HDD-1000SATA-H2	Hard Disk Drive 1TB, SATA for eneo BLR, DLR, DMR Series
	HDD-2000SATA	Hard Disk Drive 2TB, SATA for eneo BLR, DLR, DMR Series
	KBD-NSC-100	Network System Controller with 3-Axis Joystick and Jog Shuttle, 5VDC
	RAS+	Remote Administration Interface Software for DLR, DMR, DTR, DCR, DPR, DIR DVRs

Your partner for eneo products:

