

GLS-2301H

Home | Security | IP Server/Decoder | Servers

GLS-2301H
Network 1-channel Video/Audio Server, MJPEG,
H.264, Ethernet, 12VDC/24VAC, PoE

Art-Nr. 92551



Main Features

1-ch. Video/Audio Server for LAN/WAN/Internet
Simultaneous Video Streaming (H.264 & MJPEG)
Image Frame Rate: Up to 25 Fr./Sec. (720x576 Px.)
RS-485 Telemetry Control Interface
Alarm In / Outputs and Motion Detection
Integrated Web Server: 10Base-T/100Base-TX

Viewer for Monitoring, Recording and Configuration
Pre and Post Event Recording (in Client PC)
SD Socket for Local Video Storage by SD Cards
E-Mail Notification in Case of an Alarm
Basic Setting via USB Interface and Network
Power Input via Power over Ethernet & 12VDC/24VAC

Specifications

Series	eneo GL
System	PAL/NTSC
System requirements	Processor: Pentium IV, Core2 Duo; 2.8GHz; 512MB RAM; Microsoft Windows XP, Vista
Compression standard	MJPEG, H.264
Ethernet interface	10Base-T, 100Base-TX, RJ-45
Network protocols	TCP/IP, IPv4, UDP, FTP, PPPoE, ICMP, ARP, DHCP, SMTP, DDNS, DNS, RTSP, IP Filtering
Power over Ethernet	yes, IEEE 802.3af
Configuration	Via WebBrowser, Built-in WebServer
Picture adjustments	Image quality: 5 levels
Playback	via CMS Viewer Software
Resolution max.	720 x 576
Video resolution	720x576 (D1), 720x288 (2CIF), 352x288 (CIF), 176x144 (QCIF)

GLS-2301H

(Continuation Spezifications)

Image transm. rate max.	25 B./Sek.
Video inputs (amount)	1
Video inputs	1Vp-p, (C)VBS, 75ohms
Video output	1 Vp-p, (C)VBS, 75 ohms
Audio support	yes
Audio standards	u-law
Motion Detection Function	92 zones
Audio input	1x line-in
Audio output	1x Line output
Audio sampling rate	8kHz
Alarm inputs	6x TTL
Alarm processing	Alarm triggered by build-in motion detection, external alarm. Alarm notify to ANNP, e-mail, FTP, SD card, alarm out
System Integration	Comprehensive development SDK kit, including HTTP-API, Active-X control, customized Web page tool
Alarm output	6x TTL
Alarm reset input	TTL input
PTZ Support	yes
Activity detection	yes
Internal storage	yes
Digital storage media	6 MB RAM (Pre alarm memory, MJPEG), SD card
Access	16 Users simultaneous support
Serial interfaces	RS-485
Software upgrade	SD card / HTTP (Web browser) / FTP / USB
Text display	Date and time
Menu languages	German, English, Italian, French, Polish, Dutch, Spanish, Schwedish, Finnish, Hungarian, Czech, Portuguese
Password protection	yes, Multi level (administrators and users), IP filtering, HTTPS
Supply voltage	12VDC, 24VAC, PoE
Power consumption	3.0watts
Housing	-
Colour	Pantone 400U
Temperature range (Operation)	0 ~+50°C
Dimensions (HxWxD)	32x176x50mm
19" Rack mountable	no
Weight	390g
Parts supplied	PSU 100~240V/12VDC with power cord, USB cable, Viewer/installation CD, Manuals
Management Software Support	Aimetis - Symphony, Zelaris IP, NetAvis, GL-Manager, Milestone XProtect Corporate
Certificates	CE

GLS-2301H

Optional accessories

76056	ZELARIS_IP S04E	Software Extension for Zelarip_IP S04 for further 4 Cameras, max. 64 Cameras
76053	ZELARIS_IP S04	Server/Client Video Management Software Basic Version, 4 Camera Server license
76051	ZELARIS_IP V04	Video Management Software for Standalone Systems, Basic Version, 4 Cameras
76001	ZELARIS V08	Digital Video Network Crosslink, 8 Inputs, not Extentable, USB 2.0 Dongle
76002	ZELARIS V16	Digital Video Network Crosslink, 16 Inputs, not Extentable, USB 2.0 Dongle
76058	ZELARIS_IP HL-E	Extension for Control Room Client for further up to 1024 Channels max.
76047	ZELARIS_IP HL-B	Control Room Client Software, Basic Version, Up to max. 1024 Channels

