

GXB-1710M/IR

Home | Security | IP Cameras | Megapixel

GXB-1710M/IR
1/2.7" Network Camera, Bullet, Full HD, Day&Night,
3-9mm, H.264, 1920x1080p, PoE, ONVIF

Art-Nr. 200477



Main Features

1/2.7" 2.0 megapixel CMOS sensor
Resolution max. 1920 x 1080 (Full HD 1080p)
Simultaneous video streaming (H.264/MJPEG/MPEG-4)
Removeable infrared cut filter (ICR)
ROI (Region of Interest)
Integrated motion detection

Audio and alarm in-/outputs
Alarm recording (Micro SD card/SDHC)
ONVIF conformity / IP66
Integrated IR illumination
Extended temperature range -40°C to +50°C
Client management software included

Specifications

Series	eneo GX
Resolution standard	HD 1080p
System	day&night
Sensor size	1/2,7"
Imager	CMOS
Sensitivity (at 50% video signal)	0,2 Lux, (colour); 0.01Lux (B&W) at F1.2
Digital Noise Reduction (DNR)	yes
Low speed shutter	no
White balance	ATW / AWB, Indoor / Outdoor
Backlight compensation	no
Wide Dynamic Range (WDR)	no
Flickerless function	yes
IR cut filter	switchable

GXB-1710M/IR

(Continuation Spezifications)

Mirror function	On/Off switchable
Privacy zones masking	ON/OFF switchable
Activity detection	yes
Text display	11 character labels, ON/OFF switchable
Menu languages	English, German, French, Spanish, Italian, Portugese, Dutch, Swedish, Finnish, Polish, Hungarian, Romanian, Turkish, Czech, Chinese
Audio support	yes
Audio	built-in microphone, 16Bit, 8kHz
Alarm inputs	1, 1x for NO/NC contacts
Alarm outputs	1
Internal storage	Micro SD card, SD card
Compression standard	H.264, MJPEG, MPEG-4
Resolution max.	1920x1080p
Resolution	1920x1080 (16:9), 1280x720 (16:9), 800x450 (16:9), 640x360 (16:9), 480x270 (16:9), 320x180 (16:9), 1600x1200 (4:3), 1024x768 (4:3), 800x600 (4:3), 640x480 (4:3), 480x360 (4:3), 320x240 (4:3), 176x144 (4:3)
Image transmission rate max.	25 B./Sek.
Frame rate	25fps max.
Image display	Internet Explorer (Active X)
Ethernet interface	100Base-TX
Web browser	MS Internet Explorer vers. 7.0 or higher, Google Chrome (Java), Mozilla Firefox (Java), Safari (Java)
Network protocols	IPv4, HTTP, HTTPS, TCP/IP, UDP, RTP, RTSP, DHCP, NTP, FTP, SMTP, UPnP, PPPoE, ARP, DDNS, SAMBA
Stream types	H.264, MPEG-4, MJPEG multiple
Lens type	varifocal
Focal length	3 mm - 9 mm
Horizontal angle of view	77,4° - 29,8°
Pre-alarm recording	30sec. max. at 2MB/sec.
Post-alarm recording	1 to 30sec.
Serial interfaces	no
Access	10 users simultaneous support
Firmware update	via network
Password protection	3 password levels, yes
e-PTZ support	yes
Supply voltage	12VDC, 24VAC (±10%), 50/60Hz, PoE (IEEE-802.3af), 12VDC, 24VAC
Power over Ethernet	yes
Power consumption	0,5W
Temperature range (operation)	-40°C ~+50°C
Colour	Pantone Warm Grey 1C

GXB-1710M/IR

(Continuation Specifications)

Colour (housing)	RAL9003
Housing	outdoor
Protection rating	IP66
Integrated wall mount	yes
Hidden cable management	yes
Sunshield	yes
Clear Shield	yes
Management Software Support	CMS software, Zelaris, Aimetis - Symphony
SDK	SDK incl. HTTP-API and ActiveX
ONVIF	core specifications 1.02, yes
Dimensions (HxWxD)	92x97x226 mm
Parts supplied	installation CD, CMS software, PSU 100~240VAC, RJ-45 connection cable, manual
Certificates	CE
Certifications	CE

Optional accessories

70535	VT-PS12DC-8	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug
--------------	--------------------	--



VIDEOR