



IAD-5SE1008MUA

Article number: 220593

Ethernet Switch, Unmanaged, 8 x PoE, 120W, 2 x RJ45 1 Gbps uplink, Desktop

Ethernet PoE Switch, desktop application

Surge protection IEC61000-4-5 (6kV)

Gigabit Uplink Ports: 2 x RJ45

CCTV mode allows transmission up to 250m @ 10Mbps

8 x 10/100 PoE Ports IEEE 802.3af/at

Plug and Play no further settings necessary

Up to 30W per Port, Total ≤120W

Specifications

Features:	
Port mirror	no
QoS	no
SNMP	no
Network:	
Ethernet Standards	IEEE 802.3 10BaseT, IEEE 802.3u 100BaseTX, IEEE 802.ab 1000BaseT, IEEE 802.3at Power Over Ethernet (PoE+), IEEE 802.3af Power Over Ethernet (PoE)
Internal switching capacity (Mpps)	4,2 Mpps
Internal switching capacity (Gbit/s)	5,6 Gbps
VLAN	no
Interfaces / Inputs / Outputs:	
Ethernet interface	10Base-T, 100Base-TX, 1000Base-T
Ports	8x 10/100Base-TX, 2x 10/100/1000Base-T
Optical connection	none
General:	
Dimensions (HxWxD)	27x200x101,8mm
19" Rack mountable	no
Number PoE ports	8
Model	housing
Type	Layer2 switch
Weight	500g
Blower	no
Management	no
Mounting	desktop
PoE Power	120 W
Power over Ethernet	IEEE 802.3at
Supply voltage	40-57 VDC
Temperature range (operation)	-10°C ~ +55°C
Scope of delivery:	
Parts supplied	manual, PSU
Notes:	
Remarks	CCTV mode: transmission of 10Mbps @ 250m, CCTV mode, PoE Power output: 29.2W @ 1m; 25.8W @ 100m; 24.2W @ 150m; 19.9W @ 250m



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

