



ICB-62M2712M0A

Article number: 218305

1/2.8" Network Camera, 1920x1080, Day&Night, D-WDR, 2.7-12mm, Infrared, IP67

1/2.8" Sony STARVIS CMOS	Cross Web Browsing (IE, Safari, Firefox, Chrome)
Resolution max. 1920x1080	Responsive web Design, Zero configuration
Integrated connection box with circuit board	Simultaneously H.264 & MJPEG (Triple streaming)
Simple and tidy wiring	VerticalView 90° / 270°, HTML5 Playback
Motorized lens, 2.7~12 mm	LDC (Lens Distortion Correction), Defog function
Push Focus for easy lens adjustment	Slot for Micro SD memory card

Specifications

Camera:		Features:	
Camera type	Bullet	Privacy zones masking	Areas-ON/OFF switchable
Sensor size	1/2.8"	Remote configuration	web browser
Resolution standard	HD 1080p	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Imager	CMOS, Sony STARVIS, Sensor IMX291	User interface	Type A (orange / grey)
System	True Day&Night	Mirror function	mirror, flip
Sensitivity	0,15 Lux, at F1.4, 40IRE	Digital Noise Reduction (DNR)	yes
Low speed shutter	yes, automatic	Network:	
Manual electronic shutter (MES)	1/25 ~ 1/10000sec.	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Automatic electronic shutter (ESC)	1/25 ~ 1/10.000sec.	Interfaces / Inputs / Outputs:	
Wide Dynamic Range (WDR)	D-WDR	Video outputs	no
Flickerless function	yes	External connections	SD card slot, Connection board (LSA, RJ45)
Backlight compensation	BLC, HLC	Ethernet interface	10Base-T, 100Base-TX
Day/Night switching	auto, day, night, extern (Sensor), night-color mode	Alarm inputs	no
IR cut filter	switchable	Alarm outputs	no
White balance	ATW-Indoor, ATW-Outdoor, automatic, manual, Fluorescent light, Light bulb, Flammes, Shade, Clear Sky	Serial interfaces	Ethernet
Signal-to-noise ratio	50dB	General:	
Video:		Series	eneo KN-Series, eneo Candid Small
Resolution	1920x1080 (16:9), 1600x1200 (4:3), 1280x960 (4:3), 1280x720 (16:9), 960x540 (16:9), 640x360 (16:9), 320x180 (16:9)	Dimensions (HxWxD)	130,5x82,1x265,1mm
Resolution max.	1920x1080	Illumination	infrared, 4x High Power LEDs 850nm
Resolution max. [#1]	VerticalView 90°/270°, 4:3, 16:9	Illumination range	approx. 40m
Stream types	2x H.264, 1x MJPEG multiple	Colour (housing)	Pantone Cool Gray 1C
Image transmission rate max.	30 fps	Housing	outdoor
Compression standard	H.264, M-JPEG	Housing material	aluminium
Lens:		Weight	1.25kg
Lens type	Varifocal (motorized)	Integrated wall mount	yes
Zoom factor	4x	Power consumption	8W
Focal length	2,7 - 12 mm	Blower	yes
Digital zoom	16x	Mounting	wall mount, ceiling mount
MOD (Minimum object distance)	0,5 m	ONVIF	ONVIF Profile S
Iris control	DC	Power over Ethernet	IEEE 802.3af
Vertical angle of view	56 - 18 °	Window heater	yes
Horizontal angle of view	114 - 33 °	Protection rating	IP67
DORI:		SDK	upon request
Detection (25 px/m)	45 - 130 m	Hidden cable management	yes
Observation (62 px/m)	18 - 56 m	Sunshield	yes
Recognition (125 px/m)	9 - 25 m	Supply voltage	PoE
Identification (250 px/m)	4 - 13 m	Temperature range (operation)	-50°C ~ +50°C
Features:		Temperature range (heater deactivated)	-20°C ~ +50°C
Multicast compliant	yes	Text display	supplied
Motion detector	yes	Vandalism resistant	no
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, Defog	Scope of delivery:	
Alarm processing	recording internal storage, E-Mail, HTTP, FTP, Boost, TCP, UDP, Onvif Event Mapping	Parts supplied	manual, bag of screws
Audio support	no	Notes:	
Password protection	yes	Remarks	Operating temperature range of the camera changes when IR illumination is switched OFF, Please note that the automatic mode and permanent use of Zoom function may have an adverse affect on the lifetime of the camera.
e-PTZ support	yes		
Internal storage	microSDHC card, microSDXC card		
Menu languages	English, German, French, Polish, Finnish		

Related Products



PM-42A | SKU: 202641

More product information

Integrated connection box

Product recommendations



IAR-75E1024MMA | SKU: 214460



IAM-55E1008MUA | SKU: 214459



IAD-55G1004MUA | SKU: 216469



IAD-55G1008MUA | SKU: 216472




IAR-75G1008MMA | SKU: 216473



IAR-75G1016MMA | SKU: 216474



IAR-75G1024MMA | SKU: 216682



eneo Site Manager | SKU: 218218

