



IEB-74M2812MAA

Article number: 219588

1/3" Network Camera, 2592x1520, Day&Night, WDR, 2,7-12mm, Infrared, IP66

1/3" OmniVision CMOS	Micro SD Card (SDHC, SDXC)
Resolution max. 2592x1520, 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised vary focal lens 2,7~12mm with P-Iris	Infrared illumination up to 30m
Intelligent self learning video analysis (IntelliVision inside)	Easy installation, IP66
Wide Dynamic Range, T-WDR (120dB)	PoE IEEE 802.3af Class 0, 12VDC
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec ROI Hi-Stream	Supports ONVIF Profile S und Profile T

Specifications

Camera:		Features:	
Camera type	Bullet	e-PTZ support	yes
Sensor size	1/3"	Internal storage	microSDHC card, microSDXC card
Resolution standard	4 Megapixel	Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Imager	CMOS, OmniVision Sensor 4689	Privacy zones masking	Areas-ON/OFF switchable
System	True Day&Night	Remote configuration	web browser
Sensitivity	0,14 Lux, at F1.6, 40IRE	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Low speed shutter	yes, automatic	User interface	Type B (white / blue)
Manual electronic shutter (MES)	1~1/20.000sec.	Mirror function	H-flip, mirror
Automatic electronic shutter (ESC)	1~1/20.000sec.	Digital Noise Reduction (DNR)	yes
Wide Dynamic Range (WDR)	WDR 120dB	Network:	
Flickerless function	yes	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, RTP, UPnP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN
Backlight compensation	Smart BLC	Interfaces / Inputs / Outputs:	
Day/Night switching	day, night, auto	Video outputs	no
IR cut filter	switchable	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.40cm
White balance	automatic, manual	Ethernet interface	10Base-T, 100Base-TX
Video:		Alarm inputs	1
Resolution	2592x1520 (16:9), 2560x1440 (16:9), 2304x1296 (16:9), 1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 720x576 (4:3), 720x480 (4:3), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3), 352x256 (4:3), 352x240 (4:3), 320x240 (4:3)	Alarm outputs	1
Resolution max.	2592x1520	Serial interfaces	Ethernet
Resolution max. [#1]	VerticalView 90°/270°, 4:3, 16:9, 5:4	General:	
Stream types	Quad Streaming	Series	eneo SN-Series
Image transmission rate max.	30 fps	Dimensions (HxWxD)	86x90x279mm
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), M-JPEG	Illumination	infrared, 34x LED 850nm
Lens:		Illumination range	approx. 30m
Lens type	Varifocal (motorized)	Colour (housing)	white
Zoom factor	4x	Housing	outdoor
Focal length	2,7 - 12 mm	Housing material	aluminium
Digital zoom	yes	Weight	860g
MOD (Minimum object distance)	0,5 m	Integrated wall mount	yes
Iris control	P-iris, DC	Power consumption	9W
Vertical angle of view	55 - 18 °	Blower	no
Horizontal angle of view	97 - 31 °	Mounting	wall mount, ceiling mount
DORI:		ONVIF	ONVIF Profile S, ONVIF Profile T
Detection (25 px/m)	58 - 180 m	Power over Ethernet	IEEE 802.3af
Observation (62 px/m)	22 - 75 m	Window heater	no
Recognition (125 px/m)	11 - 36 m	Protection rating	IP66
Identification (250 px/m)	6 - 18 m	SDK	upon request
Features:		Hidden cable management	yes
Multicast compliant	yes	Sunshield	yes
Motion detector	yes	Supply voltage	12VDC, PoE
Analysis functions	activity detection, motion analysis, tampering protection, Trip wire plus object counting, loitering detection, intrusion, Human detector, Defog	Temperature range (operation)	-20°C ~ +50°C
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out, Alarm Forwarding (Preset Call of eneo PTZ Dome)	Text display	supplied
Audio	2 Way Audio	Vandalism resistant	no
Audio support	yes	Scope of delivery:	
Password protection	yes	Parts supplied	manual, bag of screws

Notes:	
Remarks	Note that electronic adjustment aid such as Zoom / Focus or Pan / Tilt functions are not designed for continuous operation. Permanent use may affect the life of the camera

Related Products



VT-PS12DC-10 | SKU: 70543



AK-8B | SKU: 225729



AK-9B | SKU: 225730

Product recommendations



IAR-75E1024MMA | SKU: 214460



IAM-55E1008MUA | SKU: 214459



IAD-55G1004MUA | SKU: 216469



IAD-55G1008MUA | SKU: 216472




IAR-75G1008MMA | SKU: 216473



IAR-75G1016MMA | SKU: 216474



IAR-75G1024MMA | SKU: 216682



eneo Site Manager | SKU: 218218

