



IED-68M3611MAA 7016

Article number: 225717

1/2.5" Network Dome, Fixed, 3840x2160, Day&Night, WDR, 3,6-11mm, IR, Anthracite Gray

1/2.5" Sony STARVIS CMOS	Micro SD Card (SDHC, SDXC)
4K UHD Resolution (3840x2160), 25fps frame rate	1 x Alarm in and output as well as audio support
Motorised varifocal lens 3,6-11mm with P-Iris	Infrared illumination up to 30m
Intelligent self-learning video analysis (IntelliVision inside)	PoE IEEE 802.3af Class 0, 12VDC, IP66
Wide Dynamic Range, True WDR (120dB)	Supports ONVIF Profile S and Profile T
Quad Streaming: H.264, H.265 x3, MJPEG x1, Smart Codec ROI Hi-Stream	Colour RAL 7016 anthracite gray

Specifications

Camera:		Features:	
Camera type	Dome	Audio	2 Way Audio
Sensor size	1/2.5"	Audio support	yes
Resolution standard	4K Ultra HD	Password protection	yes
Imager	CMOS, Sony STARVIS, Sensor IMX274	e-PTZ support	yes
System	True Day&Night	Internal storage	microSDHC card, microSDXC card
Sensitivity	0,03 Lux, at F1.5, 40IRE	Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Low speed shutter	yes, automatic	Privacy zones masking	Areas-ON/OFF switchable
Manual electronic shutter (MES)	1~1/20.000sec.	Remote configuration	web browser
Automatic electronic shutter (ESC)	1~1/20.000sec.	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Wide Dynamic Range (WDR)	WDR 120dB	User interface	Type B (white / blue)
Backlight compensation	Smart BLC	Mirror function	H-flip, mirror
Day/Night switching	day, night, auto	Digital Noise Reduction (DNR)	yes
IR cut filter	switchable	Network:	
White balance	automatic, manual	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, RTP, UPnP, RTSP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN
Video:		Interfaces / Inputs / Outputs:	
Resolution	3840x2160 (16:9), 3072x2048 (4:3), 2592x1944 (4:3), 2592x1520 (16:9), 2560x1440 (16:9), 1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3), 352x256 (4:3), 352x240 (4:3), 320x240 (4:3)	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.40cm
Resolution max.	3840x2160	Ethernet interface	10Base-T, 100Base-TX
Resolution max. [#1]	4:3, 16:9, 5:4	Alarm inputs	1
Stream types	Quad Streaming	Alarm outputs	1
Image transmission rate max.	30 fps	General:	
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), MJPEG	Series	eneo SN-Series
Lens:		Dimensions (HxWxD)	99x144mm
Lens type	Varifocal (motorized)	Illumination	infrared, 28x LED 850nm
Zoom factor	3x	Illumination range	approx. 30m
Focal length	3,6 - 11 mm	Colour (housing)	RAL7016
Digital zoom	yes	Colour (bubble)	clear
MOD (Minimum object distance)	0,5 m	Housing	outdoor
Iris control	P-iris, DC	Housing material	aluminium
Vertical angle of view	49 - 21 °	Weight	785g
Horizontal angle of view	87 - 38 °	Heater	no
DORI:		Power consumption	8,5W
Detection (25 px/m)	94 - 230 m	Blower	no
Observation (62 px/m)	40 - 95 m	Mounting	wall mount, ceiling mount
Recognition (125 px/m)	17 - 47 m	ONVIF	ONVIF Profile S, ONVIF Profile T
Identification (250 px/m)	9 - 23 m	Power over Ethernet	IEEE 802.3af
Features:		Protection rating	IP66
Multicast compliant	yes	SDK	upon request
Motion detector	yes	Supply voltage	12VDC, PoE
Analysis functions	activity detection, motion analysis, tampering protection, Trip wire plus object counting, loitering detection, intrusion, Human detector, Defog	Temperature range (operation)	-20°C ~ +50°C
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out, Alarm Forwarding (Preset Call of eneo PTZ Dome)	Text display	supplied
Rotation range	359 °	Vandalism resistant	yes
Vertical tilt range	0 ~ +90°	Certificates	IK10
Scope of delivery:		Scope of delivery:	
		Parts supplied	manual, bag of screws

Notes:	
Remarks	Note that electronic adjustment aid such as Zoom / Focus or Pan / Tilt functions are not designed for continuous operation. Permanent use may affect the life of the camera, Colour matching accessories on request

Related Products



VT-PS12DC-10|SKU: 70543

