



IPC-52A0030P0A

Article number: 212716

1/2.8" Network Camera, Day&Night, 1920x1080, WDR, 30x AF Zoom, 4.3-129mm, Indoor

1/2.8" Sony CMOS Sensor	Real time WDR (Wide Dynamic Range) 25/30fps
30x AF Zoom, 4.3-129mm / 16x Digital	Digital Image Stabilisation (DIS)
Full HD 1920x1080 pixels, 1080p@50/60fps	Privacy zones
Compression H.264/MJPEG, Web Casting	Alarm in- and outputs, microSD card slot
Digital Noise Reduction (DNR)	ONVIF conformity
VCA Video Analytic	

Specifications

Camera:		Features:	
Camera type	Zoom Camera	Audio support	yes
Sensor size	1/2.8"	Password protection	yes
Resolution standard	HD 1080p	e-PTZ support	yes
Imager	CMOS, Sony STARVIS, Sensor IMX291	Internal storage	microSDHC card, microSDXC card
System	True Day&Night	Menu languages	English, Korean, Chinese, Russian, German, French, Japanese
Sensitivity	0,35 Lux, 50 IRE, at F1.6	Privacy zones masking	Areas-ON/OFF switchable
Low speed shutter	yes, 2x ~ 8x	Remote configuration	web browser
Manual electronic shutter (MES)	1/25 ~ 1/30.000sec	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Automatic electronic shutter (ESC)	1/25 ~ 1/30.000sec.	User interface	Type B (white / blue)
Wide Dynamic Range (WDR)	WDR 120dB, Real Time WDR 25/30fps	Mirror function	H/V flip
Backlight compensation	BLC, HLC	Digital Noise Reduction (DNR)	yes
Day/Night switching	auto, day, night		
IR cut filter	switchable		
White balance	automatic, outdoor, manual, fluorescent, Light bulb		
Video:		Network:	
Resolution	1920x1080 (16:9), 1280x1024 (5:4), 1280x960 (4:3), 1024x768 (4:3), 1280x720 (16:9), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 640x360 (16:9), 320x240 (4:3)	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Resolution max.	1920x1080		
Resolution max. [#1]	4:3, 16:9, 5:4		
Stream types	2x H.264, 1x MJPEG multiple		
Image transmission rate max.	60 fps		
Compression standard	H.264, MJPEG		
Lens:		Interfaces / Inputs / Outputs:	
Lens type	auto focus zoom	External connections	RJ-45, voltage input, audio input/output, RS-485, alarm output, alarm input, SD card slot, video (BNC)
Zoom factor	30x	Ethernet interface	10Base-T, 100Base-TX
Focal length	4,3 - 129,0 mm	Alarm inputs	1
Digital zoom	16x	Alarm outputs	1
MOD (Minimum object distance)	1 m	Serial interfaces	RS-485, Ethernet
Iris control	DC	Serial interfaces protocols	Pelco D, Pelco P, Fastrax IIE, Fastrax
Vertical angle of view	36,4 - 1,29 °		
Horizontal angle of view	61,8 - 2,11 °		
DORI:		General:	
Detection (25 px/m)	64 - 2000 m	Series	eneo SN-Series
Observation (62 px/m)	25 - 840 m	Dimensions (HxWxD)	88.6x81x142mm
Recognition (125 px/m)	12 - 400 m	Mount	1/4" UNC-20
Identification (250 px/m)	6 - 200 m	Colour (housing)	white
		Housing	indoor
		Housing material	aluminium, plastic
		Weight	700g
		Power consumption	9W
		Blower	yes
		ONVIF	ONVIF Profile S
		Power over Ethernet	IEEE 802.3af
		SDK	upon request
		Supply voltage	PoE, 12VDC, 24VAC
		Temperature range (operation)	0°C ~ +50°C
		Text display	supplied
Features:		Scope of delivery:	
Multicast compliant	yes	Parts supplied	manual
Motion detector	yes		
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, face detection, Defog		
Alarm processing	FTP, E-Mail, HTTP, Boost, microSD card recording		
Audio	2 Way Audio		

Related Products



PS12DC-11 | SKU: 218653



WD-30 | SKU: 219504

Product recommendations



IAR-7SE1024MMA | SKU: 214460



IAM-5SE1008MUA | SKU: 214459



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472




IAR-7SG1008MMA | SKU: 216473



IAR-7SG1016MMA | SKU: 216474



IAR-7SG1024MMA | SKU: 216682



eneo Site Manager | SKU: 218218

