



IPC-55C0000M0A

Article number: 213022

1/1.8" Network Camera, 2592x1944, Day&Night, D-WDR, C/CS, Indoor

1/1.8" 5.0 Megapixel RGB Bayer Array CMOS	VerticalView 90°/270° mode only H.264, HTML5 Playback
Resolution max. 2592x1944	Digital Wide Dynamic Range (D-WDR)
C/CS lens mount, IR cut filter	LDC (Lens Distortion Correction), Defog function
Cross Web Browsing (IE, Safari, Firefox, Chrome)	Slot for Micro SD card
Responsive Web Design, Zero configuration	ONVIF conformity, PoE IEEE802.af
Triple Streaming: 2x H.264, 1x MJPEG	External input for day&night switching

Specifications

Camera:		Features:	
Camera type	Box	e-PTZ support	yes
Sensor size	1/1.8"	Internal storage	microSDHC card, microSDXC card
Resolution standard	5 Megapixel	Menu languages	French, English, German, Polish, Finnish
Imager	CMOS, Sony STARVIS, Sensor IMX178	Privacy zones masking	Areas-ON/OFF switchable
System	True Day&Night	Remote configuration	web browser
Sensitivity	0,07 Lux, at F1.5, 40IRE	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG, Mozilla: MJPEG, Google Chrome: MJPEG, Edge: MJPEG
Low speed shutter	no	User interface	Type A (orange / grey)
Manual electronic shutter (MES)	1/12.5 ~ 1/10.000sec.	Mirror function	mirror, flip
Automatic electronic shutter (ESC)	1/12.5 ~ 1/10.000sec.	Digital Noise Reduction (DNR)	yes
Wide Dynamic Range (WDR)	D-WDR	Network:	
Flickerless function	yes	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour
Backlight compensation	BLC, HLC	Interfaces / Inputs / Outputs:	
Day/Night switching	auto, day, night, extern (Sensor), night-color mode	Video outputs	no
IR cut filter	switchable	External connections	RJ-45, audio in/output, alarm in/output, voltage input, micro SD card slot
White balance	ATW-Indoor, ATW-Outdoor, automatic, manual, Light bulb, Flammes, Fluorescent light, Shade, Clear Sky	Ethernet interface	10Base-T, 100Base-TX
Video:		Alarm inputs	1
Resolution	5 Megapixel Modus @ 12,5fps, 2 Megapixel Modus @ 30fps, 3MP Mode @25fps, 2592x1944 (4:3), 2560x1440 (16:9), 2048x1536 (4:3), 1920x1440 (4:3), 1920x1080 (16:9), 1600x1200 (4:3), 1280x960 (4:3), 640x360 (16:9), 1280x720 (16:9), 800x600 (4:3), 640 x 480 VGA, 320x240 (4:3)	Alarm outputs	1
Resolution max.	2592x1944	Serial interfaces	no, Ethernet
Stream types	2x H.264, 1x MJPEG multiple	General:	
Image transmission rate max.	30 fps	Series	eneo KN-Series, eneo Candid Box
Compression standard	H.264, M-JPEG	Dimensions (HxWxD)	72x74x89mm
Lens:		Mount	2x 1/4" UNF-20
Lens type	lens not included	Colour (housing)	Pantone Cool Gray 1C
Lens mount	CS/C mount	Housing	indoor
Digital zoom	16x	Housing material	aluminium
Iris control	DC	Weight	300g
Features:		Power consumption	6W
Multicast compliant	yes	Blower	yes
Motion detector	yes	ONVIF	ONVIF Profile S
Analysis functions	motion detection, tampering protection, trip wire detection with counting and direction detection, Field detection, Defog	Power over Ethernet	IEEE 802.3af
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, Onvif Event Mapping, alarm out	SDK	upon request
Audio	2 Way Audio	Supply voltage	24VAC, 12VDC, PoE
Audio support	yes	Temperature range (operation)	-10°C ~ +50°C
Password protection	yes	Text display	supplied
Scope of delivery:		Scope of delivery:	
		Parts supplied	manual, C/CS adapter

Related Products



H04Z03NFDC-MP | SKU: 213619



PS12DC-11 | SKU: 218653



WD-30 | SKU: 219504

Product recommendations



IAR-7SE1024MMA | SKU: 214460



IAM-5SE1008MUA | SKU: 214459



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472




IAR-7SG1008MMA | SKU: 216473



IAR-7SG1016MMA | SKU: 216474



IAR-7SG1024MMA | SKU: 216682



eneo Site Manager | SKU: 218218

