



ISD-55P0010P0A

Article number: 217871

1/1.8" Network Dome, Fixed, Day&Night, 2592x1944, 360°, H.264, 1.05mm, Indoor

1/1.8" Sony STARVIS CMOS-Sensor	Compression H.264/MJPEG, Web Casting
1.05mm fixed lens FishEye camera	Cross Web-Browsing
360° Panorama view	D-WDR (Digital Wide Dynamic Range)
Integration in eneo Center Software	Framerate increase on motion detection
True Day&Night	OpenVPN support
Resolution max. 2048x1536@15fps	Compact design for indoor application

Specifications

Camera:		Features:	
Camera type	Dome	Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Sensor size	1/1.8"	Privacy zones masking	Areas-ON/OFF switchable
Resolution standard	5 Megapixel	Remote configuration	web browser
Imager	CMOS, Sony STARVIS	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
System	True Day&Night	User interface	Type B (white / blue)
Sensitivity	0,3 Lux, at F2.8	Mirror function	H-flip, mirror
Low speed shutter	no	Digital Noise Reduction (DNR)	yes
Manual electronic shutter (MES)	1~1/10000Sek.	Network:	
Automatic electronic shutter (ESC)	1~1/10.000sec.	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS
Wide Dynamic Range (WDR)	D-WDR	Interfaces / Inputs / Outputs:	
Backlight compensation	BLC, HLC	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.40cm
Day/Night switching	auto, day, night	Ethernet interface	10Base-T, 100Base-TX
IR cut filter	switchable	Alarm inputs	1
White balance	automatic, fluorescent, outdoor, manual, Light bulb	Alarm outputs	1
Video:		Serial interfaces	Ethernet
Resolution	2592x1944 (4:3), 2048x1536 (4:3), 1944x1444, 1440x1440, 1280x1024 (5:4), 1280x960 (4:3), 1024x1024, 1024x768 (4:3), 720x720, 704x576 (4:3), 640x480 (4:3)	General:	
Resolution max.	2592x1944	Series	eneo SN-Series
Resolution max. [#1]	4:3, 16:9, 5:4	Dimensions (HxWxD)	63,8x119mm
Stream types	2x H.264, 1x MJPEG multiple	Illumination	no
Image transmission rate max.	15 fps	Colour (housing)	white
Compression standard	H.264, M-JPEG	Housing	indoor
Lens:		Housing material	plastic
Lens type	fixed focal length	Weight	270g
Focal length	1,05 mm	Heater	no
Digital zoom	yes	Power consumption	5,3W
Vertical angle of view	360 °	Blower	no
Horizontal angle of view	360 °	Mounting	wall mount, ceiling mount
DORI:		ONVIF	ONVIF Profile S
Detection (25 px/m)	36 m	Power over Ethernet	IEEE 802.3af
Observation (62 px/m)	14 m	SDK	upon request
Recognition (125 px/m)	6 m	Supply voltage	12VDC, PoE
Identification (250 px/m)	4 m	Temperature range (operation)	-10°C ~ +50°C
Features:		Text display	supplied
Multicast compliant	yes	Vandalism resistant	no
Motion detector	yes	Scope of delivery:	
Analysis functions	Defog, tampering protection	Parts supplied	manual, bag of screws
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out		
Audio	2 Way Audio		
Audio support	yes		
Password protection	yes		
Internal storage	microSDHC card, microSDXC card		

Related Products



PS12DC-11 | SKU: 218653

More product information

ImmerVision certificate

Product recommendations



IAR-7SE1024MMA | SKU: 214460



IAM-5SE1008MUA | SKU: 214459



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472




IAR-7SG1008MMA | SKU: 216473



IAR-7SG1016MMA | SKU: 216474



IAR-7SG1024MMA | SKU: 216682



eneo Site Manager | SKU: 218218

