



ISD-59P0010P0A

Article number: 220196

1/1,7" Network Dome, fixed, Day/Night, 4000x3000, H.265, 1,29mm, 360°, infrared, IP66

1/1.7" Sony STARVIS CMOS-Sensor	Quad Stream (H.264/H.265x3, MJPEGx1)
1.29mm fixed lens FishEye camera	Cross Web-Browsing
360° Panorama-, Corridor-, Quad-, Panomorph-View, ceiling or wall	True-WDR (Digital Wide Dynamic Range)
Integration in eneo Center Software	Framerate increase on motion detection (Smart Codec)
True Day & Night	IR-LED Illumination integrated
Resolution max. 4000x3000@20fps	Compact design for indoor application

Specifications

Camera:		Features:	
Camera type	Dome	Password protection	yes
Resolution standard	4K Ultra HD	Internal storage	microSD card, microSDXC card
Imager	CMOS, Sony STARVIS, Sensor IMX226	Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
System	True Day&Night	Remote configuration	web browser
Sensitivity	0,3 Lux, at F2.8	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Low speed shutter	yes, automatic	Digital Noise Reduction (DNR)	yes
Manual electronic shutter (MES)	1~1/20.000sec.	Network:	
Automatic electronic shutter (ESC)	1~1/20.000sec.	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, UPnP, RTP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS
Wide Dynamic Range (WDR)	WDR 120dB	Interfaces / Inputs / Outputs:	
Backlight compensation	BLC	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx. 40cm
Day/Night switching	auto, day, night	Ethernet interface	10Base-T, 100Base-TX
IR cut filter	switchable	Alarm inputs	1
White balance	automatic, fluorescent, manual, outdoor, incandescent	Alarm outputs	1
		Serial interfaces	Ethernet
Video:		General:	
Resolution	4000x3000 (4:3), 3000x3000, 2560x2560,, 2160x2160, 2048x2048, 1280x1280, 640x640, 480x480	Series	eneo SN-Series
Resolution max. [#1]	360° Panorama, 2x 180° Panorama, 360° +3PTZ, VerticalView 90°	Dimensions (HxWxD)	58,7x151,4mm
Stream types	Quad Streaming	Illumination	infrared, 6x LEDs 850nm
Image transmission rate max.	30 fps	Illumination range	approx. 10m
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), M-JPEG	Colour (housing)	white
Lens:		Housing material	metal
Lens type	fixed focal length	Weight	750g
Focal length	1,29 mm	Heater	no
Digital zoom	yes	Power consumption	12.5W @ PoE,, 15W @ VDC12V
MOD (Minimum object distance)	0,1 m	Blower	no
Iris control	DC	Mounting	wall mount, ceiling mount
Horizontal angle of view	360 °	ONVIF	ONVIF Profile S
DORI:		Power over Ethernet	IEEE 802.3af
Detection (25 px/m)	60 m	Protection rating	IP66
Observation (62 px/m)	25 m	Supply voltage	12VDC, PoE
Recognition (125 px/m)	11 m	Temperature range (operation)	-20°C ~ +50°C
Identification (250 px/m)	5 m	Text display	supplied
Features:		Vandalism resistant	yes
Multicast compliant	yes	Certificates	IK10
Motion detector	yes	Scope of delivery:	
Analysis functions	activity detection, motion analysis, tampering protection, Trip wire plus object counting, loitering detection, intrusion, Human detector, Defog	Parts supplied	manual, bag of screws
Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out		
Audio	2 Way Audio		
Audio support	yes		

Related Products



PS12DC-11 | SKU: 218653



AK-8B | SKU: 225729



AK-9B | SKU: 225730

Product recommendations



IAR-7SE1024MMA | SKU: 214460



IAM-5SE1008MUA | SKU: 214459



IAD-5SG1004MUA | SKU: 216469



IAD-5SG1008MUA | SKU: 216472




IAR-7SG1008MMA | SKU: 216473



IAR-7SG1016MMA | SKU: 216474



IAR-7SG1024MMA | SKU: 216682



eneo Site Manager | SKU: 218218

