



ISM-54F0023W0A

Article number: 221437


1/3" Network Board Camera, 2592x1520, Day&Night, WDR, 2,3mm, H.265, PoE, 12VDC

1/3" 4.0 MP Omnivision CMOS-Sensor	WDR 120dB, Smart BLC
Resolution max. 2592x1520	Slot for Micro SD memory card
Board Camera 50x50x60,4mm	ONVIF conformance, PoE IEEE802.af, 12VDC
Quad Streaming (H.265, H.264, MJPEG)	Audio-, Alarm- In- and Outputs
True Day & Night (TDN)	Privacy zones, password protection, Cross Web-Browsing
Noise Reduction (2D-/3D-DNR)	Framerate increase on motion detection

Specifications

Camera:		Features:	
Camera type	Platine	Alarm processing	recording internal storage, E-Mail, FTP, Boost, HTTP, TCP, UDP, HTTPS, XML, alarm out
Sensor size	1/3"	Audio	2 Way Audio
Resolution standard	4 Megapixel	Audio support	yes
Imager	CMOS, OmniVision Sensor 4689	Password protection	yes
System	True Day&Night	e-PTZ support	yes
Sensitivity	0,25 Lux, 40IRE	Internal storage	microSDHC card, microSDXC card
Low speed shutter	yes, automatic	Menu languages	English, German, French, Russian, Chinese, Korean, Japanese
Manual electronic shutter (MES)	1~1/10000Sek.	Privacy zones masking	Areas-ON/OFF switchable
Automatic electronic shutter (ESC)	1~1/10.000sec.	Remote configuration	web browser
Wide Dynamic Range (WDR)	WDR 120dB	Web browser	MS internet Explorer: ActiveX ex 9.0, Safari: MJPEG setup limited, Mozilla: MJPEG setup limited, Google: MJPEG setup limited, Edge: MJPEG setup limited
Flickerless function	yes	User interface	Type B (white / blue)
Backlight compensation	Smart BLC	Mirror function	H-flip, mirror
Day/Night switching	auto, day, night	Digital Noise Reduction (DNR)	yes
IR cut filter	switchable		
White balance	automatic, manual		
Signal-to-noise ratio	50dB		
Video:		Network:	
Resolution	2592x1520 (16:9), 2560x1440 (16:9), 2304x1296 (16:9), 1920x1080 (16:9), 1440x1080 (4:3), 1280x1024 (5:4), 1024x768 (4:3), 1280x720 (16:9), 800x600 (4:3), 800x480 (16:9), 720x576 (4:3), 720x480 (4:3), 704x576 (4:3), 704x480 (4:3), 640x480 (4:3), 400x240 (4:3), 352x288 (4:3), 352x256 (4:3), 352x240 (4:3), 320x240 (4:3)	Network protocols	TCP/IP, UDP, IPv4, IPv6, HTTP, HTTPS, FTP, RTP, UPnP, RTSP, RTCP, DHCP, ARP, Zeroconf, Bonjour, QoS, OpenVPN
Resolution max.	2592x1520		
Resolution max. [#1]	VerticalView 90°/270°, 4:3, 16:9, 5:4		
Stream types	Quad Streaming		
Image transmission rate max.	30 fps		
Compression standard	H.264, H.265, H.264+ (Smart Stream), H.265+ (Smart Stream), M-JPEG		
Lens:		Interfaces / Inputs / Outputs:	
Lens type	fixed focal length	Video outputs	no
Focal length	2,3 mm	External connections	alarm output, alarm input, audio input/output, RJ-45, 12VDC input (DC plug), connection cable approx.55cm
Digital zoom	yes	Ethernet interface	10Base-T, 100Base-TX
MOD (Minimum object distance)	0,3 m	Alarm inputs	1
Iris control	no	Alarm outputs	1
Vertical angle of view	75 °	Serial interfaces	Ethernet
Horizontal angle of view	130 °		
DORI:		General:	
Detection (25 px/m)	28 m	Dimensions (HxWxD)	50x50x60,4mm
Observation (62 px/m)	11 m	Illumination	no
Recognition (125 px/m)	5 m	Housing	without housing
Identification (250 px/m)	2,5 m	Weight	70g
		Power consumption	4.8W
		Blower	no
		ONVIF	ONVIF Profile S
		Power over Ethernet	IEEE 802.3af
		SDK	upon request
		Supply voltage	12VDC, PoE
		Temperature range (operation)	0°C ~ +40°C
		Text display	supplied
		Vandalism resistant	no
Features:		Scope of delivery:	
Multicast compliant	yes	Parts supplied	manual, Connection cable set
Motion detector	yes		
Analysis functions	motion analysis, intrusion, tampering protection, Defog		

Product recommendations



eneo Site Manager | SKU: 218218



eneo is a registered trademark of
VIDEOR E. Hartig GmbH
Carl-Zeiss-Straße 8
63322 Rödermark, Deutschland

Phone: +49 6074 - 888 - 300
Fax: +49 6074 - 888 - 100
E-Mail: info@eneo-security.com
Web: www.eneo-security.com

Stay informed and subscribe
to the eneo newsletter

