

Video Security



VK-1319

1/3" B/W Cylinder Camera with 3.6mm Lens, 12VDC, 420TVL

Art-No. 91866



Features

CCD B&W Cylinder Camera with Integrated Lens
1/3" Super HAD CCD Sensor
Resolution of 420 Horizontal Lines
Automatic Shutter Control (AES)
H & V Aperture (APC)

Internal Synchronization
High Sensitivity of 0.65 Lux (F2.0)
Supply Voltage: 12 VDC
Weatherproof Aluminium Housing
Mounting Stand with Swivel Head

Specifications

Cable connection	Wiring for video and voltage supply made, accessible from outside (approx. 0.5m long, Video: BNC jack; 12/24V input: for DC plug 2.1/5.5mm)
System	CCIR
Imager	1/3" Sony Super HAD Interline Transfer CCD
Active picture elements	Approx. 290,000 (H) 500 x (V) 582
Synchronization	Internal
Gamma correction	0.45
Horizontal resolution	420 TV lines
Sensitivity at 50% video signal	0.65Lux at F2.0 / 0.23Lux bei F1.2 (VT measurement result)
Automatic gain control (AGC)	Yes
Integrated lens	F 2.0/3.6 mm
Horizontal angle of view	69°
Video output	1 Vp-p, VBS, 75 ohms
Supply voltage	12 VDC (+/- 10%)
Power consumption	1.2watts
Protection rating	IP67
Housing	Aluminium

(Specifications continued)

Colour	Black
Temperature range	-10°C to +50°C
Dimensions (LxD)	60x19 mm
Weight	55 g (incl. stand)

Accessories

77779 / VT-PS12DC-UK	Power Supply Unit w. UK Mains plug-in, 100-240VAC/12VDC-1.0A, Regul., open Ends
70447 / VT-PS12DC-5	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug