

Video Security



VK-133

1/3" B/W Board Camera with 3.8mm Lens
12VDC, 420TVL

Art-No. 91746



Features

CCD B&W Board Camera
1/3" CCD Sensor
Resolution of 420 Horizontal Lines
Electronic Shutter Control (ESC)
Internal Synchronization

High Sensitivity
Interchangeable Lens Element
Supply Voltage: 12VDC
Compact Version

Specifications

System	CCIR
Imager	1/3" Sony Super HAD Interline Transfer CCD
Active picture elements	Approx. 290,000 (H) 500 x (V) 582
Synchronization	Internal
Gamma correction	0.45
Horizontal resolution	420 TV lines
Sensitivity at 50% video signal	1.6Lux at F2,0 (VT measurement result); 0.58Lux at F1.2
Electronic shutter control (ESC)	1/50 ~ 1/100,000sec.
Aperture Correction (APC)	Yes
Integrated lens	F2.0/3.8mm
Horizontal angle of view	65°
Video output	1Vp-p, VBS, 75ohms
Supply voltage	12VDC (+/-10%)
Power consumption	1.2watts
Temperature range	-10°C ~ +50°C
Dimensions (HxWxD)	32x32x25mm
Weight	30g

Accessories

40059 / H0225M	F2.5/2.5mm Board Camera Lens, 1/3" M12X0.5
40061 / H0820M	F2.0/8mm Board Camera Lens, 1/3" M12X0.5
79498 / VHP-1	Candid Junior I Weatherproof Housing with Wall Mount WD-21
77779 / VT-PS12DC-UK	Power Supply Unit w. UK Mains plug-in, 100-240VAC/12VDC-1.0A, Regul., open Ends
40072 / H0620M	F2.0/6mm Board Camera Lens, 1/3" M12x0.5
70448 / VT-PS12DC-6	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, w. Open Ends
77772 / VT-PS12DCDT	PSU 12VDC/0,5A, Regulated, Desktop Version, 1.8m Cable each w. open ends