



VKC-1365T

Article-No.: 92524

1/3" Colour Closeup Tower Camera with
2.9mm Lens, 12VDC, 540TVL

Mainfeatures

Colour Tower Camera for Facial Recognition
Light Sensitivity of 0.1Lux at F1.2
Automatic Shutter Control (ESC)
Automatic White Balance (AWB)
Supply Voltage: 12VDC

1/3" Super HAD CCD Sensor
Automatic Gain Control (AGC)
Fixed Backlight Compensation (BLC)
Internal Synchronization
Black, Vertically Adjustable Aluminium Enclosure


Specifications

System	Colour
Video standard	PAL
Signal processing	Digital (DSP)
Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD Interline Transfer
Active picture elements	480,000, 795(H) x 596(V)
Synchronization	Internal
Signal-to-noise ratio	50dB (AGC OFF)
Gamma correction	0.45
Horizontal resolution	540 TVL
Sensitivity (at 50% video signal)	0.1Lux at F1.2 (Videor measurement result)
Electronic shutter control (ESC)	1/50 - 1/100,000sec.
Integration rate	no
Automatic gain control (AGC)	Available
Digital Noise Reduction (DNR)	no
Automatic white balance (AWB)	Available

Specifications (continued)

Backlight compensation	BLC
Aperture Correction (APC)	Horizontal and vertical
IR cut filter	standard
Video outputs (type)	CVBS
Video outputs	1Vp-p, composite, 75ohms, BNC
Lens type	fixed focal length
Lens	F3.0 / 2.9mm
Lens mount	integrated lens
Focal length	2,9 mm
Horizontal angle of view	96,2°
Iris control	no
Filter screw size	not available
MOD (Minimum object distance)	0,2 m
Serial interfaces	no
External adjustments	-
External connections	Video (BNC), 12V (DC plug)
Protection rating	IP40
Protection rating	-
Supply voltage	12VDC
Power consumption	1.5watts
Rotation range	+/-45°
Tilt range	+/-10° (Lens)
Temperature range (Operation)	0 ~ +40°C
Housing material	Aluminium, Plastic
Housing	Indoor
Integrated wall mount	no
Hidden cable management	yes
Window heater	no
Hidden Cable Management Support	yes
Colour (housing)	black
Dimensions (HxWxD)	491-669x74x74mm
Weight	1.05kg
Parts supplied	PSU 100~240V/12VDC, Drilling template, Manual
Certificates	CE

Optional Accessories

Image	Artikel-Nr. / Typ	Description
	VT-PS12DC-8	Plug-in Power Supply Unit 100-240VAC 12VDC (1.0Amp), Regulated, with DC Plug

Your partner for eneo products:

