



VKCD-1330-2811

Article-No.: 92759

1/3" Dome, Fixed, Day&Night,
clear, 2.8-11mm, 600TVL,
Vandal Resistant, 12V

Mainfeatures

1/3" Super HAD II colour/b&w CCD sensor
High sensitivity of 0.3Lux@F1.2
Digital noise reduction (DNR)
Wide dynamic range (D-WDR)
RS-485 interface (Pelco D&P protocol)
Supply voltage: 12 VDC

Varifocal lens F1,2/2,8-11mm with DC iris
Menu-operated setup
Backlight compensation (BLC & HLBC)
Automatic white balance (AWB)
Manual 3-axis adjustment
For ceiling/wall mount

Specifications

System	day&night
Video standard	PAL
Sensor size	1/3"
Imager	CCD
Imager	Sony Super HAD II Interline Transfer
Active picture elements	795(H) x 596(V) pixels
Horizontal resolution	600 TVL
Signal-to-noise ratio	>50db
Sensitivity (at 50% video signal)	0,27 Lux
Sensitivity (at 50% video signal)	(colour), 0.2Lux (B&W) at F1.2 (measured)
Exposure modes	automatic, manual
Automatic electronic shutter (ESC)	1/50 - 1/100,000sec.
Manual electronic shutter (MES)	1/50 - 1/100,000sec.
Low speed shutter	no
Digital Noise Reduction (DNR)	yes
Digital Noise Reduction (DNR)	ON/OFF switchable

Specifications (continued)

Backlight compensation	BLC, HLC
Backlight compensation	ON/OFF switchable
Wide Dynamic Range (WDR)	yes
Wide Dynamic Range (WDR)	D-WDR (Digital Wide Dynamic Range)
White balance	ATW, manual
Blemish compensation	pixel compensation ON/OFF selectable
IR cut filter	OLPF (Overlay Low Pass Filter)
Privacy zones masking	8 zones masking
Menu languages	English, Chinese
OSD function control	OSD camera setup
Text display	16 character label
Activity detection	yes
Motion detector	4 zones, ON/OFF switchable
Mirror function	horizontal
Digital zoom	no
Lens type	varifocal
Focal length	2,8 mm - 11 mm
Horizontal angle of view	81,2° - 24,6°
MOD (Minimum object distance)	0,5 m
Video outputs	composite (CVBS)
Video outputs	1Vp-p (C)VBS, 75ohms, BNC
Alarm inputs	no
Alarm outputs	no
Rotation range	359°
Vertical tilt range	0 ~ +90°
Illumination	no
External connections	video (BNC), 12VDC power input
Serial interfaces	RS-485
Serial interfaces protocols	Pelco P, Pelco D
Housing	outdoor
Housing material	aluminium
Colour (bubble)	clear
Colour (housing)	Pantone Cool Gray 1C
Heater	no
Blower	no
Mounting	wall mount, ceiling mount, flush mount
Supply voltage	12VDC
Supply voltage	(+/-10%)
Power consumption	1.2W
Temperature range (operation)	-10°C ~ +50°C
Protection rating	IP67
Vandalism resistant	yes
Dimensions (HxWxD)	see drawing
Weight	1.05kg
Certificates	CE



Your partner for eneo products:

