

# Video Security



## VMC-15HR/1

15"(38cm) Colour Monitor, Composite, Y/C, Audio Inputs, 650TVL

Art-No. 90441



## Features

15" High Resolution Picture Tube  
Resolution of 650 Horizontal Lines  
Automatic PAL/NTSC Selection  
Video/Audio Loop-through Inputs  
Over/Underscan Function

Built-in Comb Filter  
Built-in Loudspeaker  
Universal Voltage Input: 100 to 240VAC, 50/60Hz  
Detachable Power Cord  
Rugged Metal Housing

## Specifications

Picture tube type (CRT)	90° In-line tube (0.28mm DOT pitch)
Screen size	15" (38cm)
Video standard	PAL/NTSC
PAL/NTSC signal selection	Automatic
Scanning frequency range H/V	15.625 / 50Hz, 15.750 / 60Hz
Horizontal resolution	650 TV lines at center
Video inputs	2x 1Vp-p, CVBS, automatic 75ohms termination (loop-through), Y/C input, 4-pin Mini DIN, 75ohms (loop-through)
Audio inputs	2x 300mVrms, Cinch (loop-through)
Connectors	2x Video and audio loop-trough inputs (BNC/Cinch), Y/C loop-trough input (4-pin MINI DIN), Power input
Synchronization	Internal
Audio output power	2watts
Over-/Underscan	7% / 3%
On-screen display	5 languages
LED indication	Sources selected, Power ON/OFF
Operations (Front part)	On-screen menu, Menu selection, Input selectors, Power ON/OFF
Operations (back part)	-

## VMC-15HR/1

(Specifications continued)

<b>Supply voltage</b>	100 to 240VAC, 50/60Hz
<b>Power consumption</b>	75watts
<b>Temperature range</b>	0°C to +40°C
<b>Housing</b>	Steel (with plastic front)
<b>Colour</b>	Pantone Coolgrey 7C
<b>Dimensions (HxWxD)</b>	349x362x385mm
<b>Weight</b>	14.5kg

VIDEOR TECHNICAL E. Hartig GmbH  
Carl-Zeiss-Straße 8 · 63322 Rödermark · Germany  
Telefon +49 (0) 60 74/8 88-0 · Telefax +49 (0) 60 74/8 88-100  
info@videortechnical.com · www.videortechnical.com

