

Quads



► **EP 4BQ - 4-channel b/w
quad Processor**

Specifications

Video format: CCIR

Video input: 4 inputs with loop-through
1 VCR input, 1 Vp-p, 75 Ohm

Video output: 1 monitor output
1 quad output for VCR, 1 Vp-p at 75 Ohm

Refresh rate: 15-30 fields / sec.

VCR playback: yes

Alarm input: 4 alarm inputs

Alarm output: 1x NO/NC relay output

Power source: 24 V AC, 230 V AC via included power supply

Power consumption: max. 5 W

Ambient temperature: 0°C ~ +50°C

Dimensions: 239 (W) x 55 (H) x 166 (D) mm

Weight: 2,0 kg



► **EP 4CQ - 4-channel colour
quad processor**

Specifications

Video format: PAL

Video input: 4 inputs, 1 Vp-p, 75 Ohm
1 VCR input, 1 Vp-p, 75 Ohm

Video output: 2 video outputs, 1 Vp-p at 75 Ohm

Title: 6-character title generator for each camera

Timer: built-in real time clock

Alarm input: 4 alarm inputs

Alarm output: 1 NO/NC relay output

Power source: 12 V DC / 24 V AC,
230 V AC via included power supply

Power consumption: 17 W max.

Ambient temperature: 0°C ~ +50°C

Dimensions: 239 (W) x 55 (H) x 166 (D) mm

Weight: 2,4 kg