

Product information

Focusing on
tomorrow, caring
for today

EP 8BDX

8-channel b/w duplex multiplexer,
incl. IR remote control



Specifications

Video format: CCIR

Display format: 1, 4, 4+4, 9

Video input: 8 inputs with loop-through, 1 Vp-p, 75 Ohm
1 VCR input, 1 Vp-p, 75 Ohm

Video output: 8 loop-through outputs 1 Vp-p at 75 Ohm

Monitor output: 1 x main monitor, 1 x call monitor

VCR output: multiplexed, 1 Vp-p at 75 Ohm

Resolution: 960 x 576

Refresh rate: 50 fields / sec.

VCR playback: 1, 4, 4+4, 9

Playback zoom function: yes

Time-lapse recording: adjustable

Dynamic recording priority: yes

Title: 8 characters title generator for each camera

Timer: built-in real time clock

Alarm input: 8 alarm inputs, 1 alarm reset input

Alarm output: 1 NO/NC relay output

Freeze function: yes

Video loss detection: yes

Motion detection: 192 targets per camera (16 x 12)

Setup: on-screen display

Sequential switch: programmable auto sequential switch
with adjustable dwell time (1 ~ 99 sec.)

Key lock: yes

Remote control: 9-pin Sub-D / RS-232, IR remote control

Power source: 24 V AC, 230 V AC via included power supply

Power consumption: 17 W max.

Operating temperature: 0°C ~ +50°C

Dimensions: 438 (W) x 44 (H) x 262 (D) mm

Weight: 5,0 kg