

**SPECIFICATIONS**

Pickup Device	: 1/3", Super HAD CCD
Picture element	: 582(H) x 500(V)
Scanning	: 2:1 interlaced
Video Output	: 1Vpp composite CCIR, BNC
Audio	: microphone output 500mV / 47KOhm, 40Hz-12KHz (-3dB), Cinch
S/N Ratio	: > 48 dB
Horizontal resolution	: 420 TVL
Sensitivity	: 0,04 Lux / F1,2
BLC	: ON / OFF
AGC	: ON / OFF
Synchronisation	: internal or Line-Lock with V-adjustment
Electronic shutter	: ON / OFF, up to 1:100.000
Flickerless function	: ON / OFF
Gamma correction	: > 0,45
Lens drive	: Direct Drive / Video Iris
Lens mount	: C / CS
Power source	: EQ120 C/A: 24 VAC / 12 VDC EQ120 C : 90 ~ 260VAC
Power consumption	: EQ120 C/A: 5 W max. EQ120 C : 9 W max.
Operating temperature	: 0°C ~ 50°C
Dimensions	: 57 (W) x 51 (H) x 140,2 (D) mm

Due to continued improvement, specifications are subject to change without prior notice.

EverFocus® Electronics (Europe) GmbH

Albert-Einstein-Str. 1, 46446 Emmerich

Phone: +49 (0) 2822 9394-0, Fax: +49 (0) 2822 9394-95

Internet: www.everfocus.de, email: info@everfocus.de