

# Product information

- FH 7153 H - outdoor housing HOV with sunshield and heater, side opening
- FH 7154 H - outdoor housing HEM with sunshield and heater
- FH 7156 H/B - outdoor housing HEB with sunshield, heater and cable channel
- FH 7160 - dustproof housing HEM
- FH 7161 / B - dustproof housing HEB with cable channel



FH 7153 H



FH 7154 H



FH 7156 H/B



FH 7160



FH 7161 / B

## Technical data

	FH 7153 H	FH 7154 H	FH 7156 H/B	FH 7160	FH 7161 / B
Outer dimensions (WxHxL)	163 x 115 x 412 mm	105 x 95 x 355 mm	138 x 128 x 410 mm	105 x 95 x 355 mm	138 x 128 x 410 mm
Inner dimensions (WxHxL)	100 x 70 x 250 mm	70 x 65 x 300 mm	90 x 85 x 320 mm	70 x 65 x 300 mm	90 x 85 x 320 mm
Dimensions sunshield (WxHxL)	176 x 98 x 514 mm	113 x 71 x 410 mm	144 x 90 x 470 mm	-	
Material	Extruded and die-cast aluminium				
Colour	Powder-coated RAL 9002				
Weatherproof rating	IP 66			-	
Ambient temperature	-20°C ~ +50°C			0°C ~ +50°C	
Heater	Thermostat-controlled, 115 ~ 240 V AC, 40 W				-
Weight	3,0 kg	1,9 kg	2,2 kg	1,4 kg	1,8 kg


### FH 7165 – sunshield HEM

Dimensions (WxHxD)	113 x 71 x 410 mm
Weight	0,5 kg
Material	Extruded aluminium
Colour	Powder-coated RAL 9002



### FH 7167 – power supply HEM

Power supply input	230 V AC
Power supply output	12 V DC / 400 mA, stabilized



### FH 7166 / B – sunshield HEB

Dimensions (WxHxD)	144 x 90 x 470 mm
Weight	0,9 kg
Material	Extruded aluminium
Colour	Powder-coated RAL 9002

### FH 7168 / B – power supply HEB

Power supply input	230 V AC
Power supply output	12 V DC / 400 mA, stabilized

### FH 7101 H – thermostat heater HEM/HEB

Power supply input	12 V DC / 24 V AC
Power consumption	20 W



FH\_db\_en\_rev00