

EXTERNAL DOORLOCK RELAY MEET

**Reference:** 1490

The DUAL RELAY MEET MODULE can be installed as an auxiliary element for MILO/KIN w/keypad panels or MILO 1W panels, as well, having a different performance in each case:

MILO/KIN DIGITAL panles

When...

DESCRIPTION

The DUAL RELAY MEET MODULE can be installed as an auxiliary element for MILO/KIN w/keypad panels or MILO 1W panels, as well, having a different performance in each case:

MILO/KIN DIGITAL panles

When installed indoors, it works as a security device, since the electric lock is controled directly from a relay of this device instead of the relay in the panel.

In that way is not posible to manipulate the wires of panel, installed outdoor, for opening the door maliciously.

MILO 1W panels

Relay 1 is activated simultaneously with the panel relay, when the door is opened from the monitor.

Relay 2 allows the control of a secondary electric lok for the garage, garden, etc.

In both cases, it is also posible to activate manually the relays by means of exit pushbuttons.

TECHNICAL SPECIFICATIONS

- Power: 12 Vdc/ 1W
- Operating temperature: -40° C-70° C
- Humidity: 20%-80%
- Protection: IP30:
- Size: 114,5 x 56,5 x 34 mm
- Weight: 110 gr

Weight: 0,1687 kg

Size of product when packed: 12x6,3x3,8 cm

EAN 13: 8424299014906