

## COLOUR DUOX VEO-XS MONITOR 4,3"

**Reference: 9408**

Hands-free VEO-XS monitor. Characterised by its small size and extra-flat thickness. Thanks to its OSD menu and the layout of the buttons, interaction with the user is simple and intuitive. Made of...

### DESCRIPTION

Hands-free VEO-XS monitor. Characterised by its small size and extra-flat thickness. Thanks to its OSD menu and the layout of the buttons, interaction with the user is simple and intuitive. Made of high impact ABS plastic. Texturised finish for easy cleaning and ultraviolet protection. Surface installation. VEO-XS incorporates a 4,3" (16:9) panoramic color TFT screen. Its balanced design of pure lines is distinguishing, modern and minimal. VEO-XS integrates in the ambience. When a call is received, the image appears automatically. When the conversation button is pressed a conversation with the visitor can take place. The image is de-activated automatically after 90 seconds, or when the button is pressed again. To open the door, press the button key.

**ACCESSORIES****CONNECTOR**

9407 DUOX VEO-XS MONITOR CONNECTOR

Necessary to mount the monitor on the wall surface.

**REPLACEMENT**

3388 UNIVERSAL FRAME 120X240

Universal frame with an extra slim format, it is manufactured in a high resistant ABS plastic with a texturised finish. In replacement works, allows to cover the space left by older equipment. In addition, it keeps the wall protected from the dirt produced by the use of telephones and monitors. Dimensions: 120 x 240 x 10 mm.

3389 UNIVERSAL LARGE FRAME 120x240

Dimensions: 120 x 240 x 10 mm

### TECHNICAL SPECIFICATIONS

**GENERAL CHARACTERISTICS**

Technology DUOX (non-polarized 2 wire full digital system)

Audio/Video system Audio/Video Color

Set-up (Installation) Surface mounted (connector ref. 9407)

Desktop support -

Handset with magnet to facilitate the hang up -

Hands-free communication Yes

Press-to-talk communication configurable Yes

Induction loop included Yes (FFR09408)



Screen dimensions 4,3" (Panoramic 16:9)  
Screen resolution (H x V) 480 x 272  
Color of the product Matt white  
Number of pushbuttons 5  
Kind of pushbuttons Mechanical (silicon)  
Number of leds for lighted indications 3 (red, blue and green)

## PROGRAMMING OF THE TERMINAL ADDRESS

From the terminal From the OSD menu  
From the outdoor panel or guard unit Yes  
From the outdoor panel throughout the apartment door bell Yes

## FEATURES

Automatic picture capture when the visitor calls (PHOTOCALLER) Yes (1 photo/call, until 150 photos, 320 x 240 pixels)  
Guard unit call Yes (by means of the door release button)  
Auto-on Yes (with 3 outdoor panels)  
OSD menu Yes  
Additional function F1 Yes (Button F1 sends a negative and/or command)  
Additional function F2 Yes (it only sends command, no negative)  
Apartment door bell Yes  
Connection for additional devices (call extension, light/buzzer activator, etc.) Yes  
Doormatic (automatic door release for offices, etc.) Yes (configurable until 12h)

## ADJUSTMENTS

Date and time Yes  
Ring tones selection Yes (5)  
Call volume control Yes (8 levels by OSD menu and sliding wheel)  
Do-not-disturb mode Yes (by OSD menu)  
Audio volume control Yes (8 levels by OSD menu and sliding wheel)  
Brightness, color and contrast control Yes (by OSD menu)

## TECHNICAL FEATURES

Product dimensions (width x height x depth) mm 125 x 165 x 21  
Time to answer or open the door since the call is done 30 s.  
Conversation time 90 s.  
Conversation privacy Yes  
Voltage 18 Vdc  
Maximum consumption (mA) 370  
Standby consumption (mA) 38  
Working temperature (°C) [-5°C, +40°C]  
Humidity [0%, 90%]  
Product Weight (kg) 0,29  
Line adaptor included in the terminal Yes (default position OFF)  
Connections Bin, Bin, Bout, Bout, -, A+, F1, T

**Weight:** 0,2949 kg

**Size of product when packed:** 17,6x12,8x3,4 cm

**EAN 13:** 8424299094083