

CB-3102

FLIR *Ariel*[™]

1080P WDR Bullet Camera



**HIGHEST QUALITY. LOWEST BANDWIDTH.
PREDICTABLE STORAGE.**

The Ariel camera series sets a new standard in its class. Featuring full HD 1080p video, Ariel cameras guarantee frame rates in high motion, complex and low light scenes thereby lowering overall utility costs and carbon footprint.

Through its motion processing architecture, CB-3102 cameras deliver predictable storage, reducing the Total Cost of Ownership (TCO).

Now you can... deploy a Full HD 1080p surveillance camera that easily handles wide variations in motion and lighting found in airports, city surveillance projects, critical infrastructure sites, commercial offices and campuses utilizing the most technologically advanced HD IP camera.

Key Features

- Multi-streaming at the highest frame rates
- Full HD 1080p at the lowest bit rate
- Included analytics:
 - Tamper Detection
 - Multi-zone VMD
 - Wide Dynamic Range
 - IR Illumination
 - Indoor/Outdoor
 - Storage on Edge
- Web interface for viewing and configuration

Features	Benefits
<ul style="list-style-type: none">• Multi-stream H.264 video	<ul style="list-style-type: none">• Crisp, clean video for supreme identification
<ul style="list-style-type: none">• Guaranteed frame rates in complex, high motion scenes	<ul style="list-style-type: none">• Maintains evidentiary integrity of video in challenging surveillance conditions
<ul style="list-style-type: none">• Motion processing	<ul style="list-style-type: none">• Maintains lowest bit rates regardless of motion/scene complexity; lowers TCO with predictable storage and network requirements
<ul style="list-style-type: none">• Auto-tune technology	<ul style="list-style-type: none">• Best out-of-the-box experience with no adjustments; auto scene adaptation eliminates service calls
<ul style="list-style-type: none">• IR model delivers more uniform high quality illumination	<ul style="list-style-type: none">• Reduces utility costs, carbon footprint and TCO

General Specifications

Camera	
Image Sensor	1/2.8" BSI CMOS
Sensor Resolution	2048 x 1536
Scanning Mode	Progressive
Sensitivity	0.03 (color)/0.01 (BW), 0 Lux with IR illuminator ON, measured at 30 IRE
Lens Type	CB-3102-01-I: Fixed 2.8mm, 102° HFOV, F1.8, D/N CB-3102-11-I: Varifocal 3-10mm, 92°-27° HFOV, F1.4, D/N, Motorized with auto-focus and auto-iris
Automatic Electronic Shutter (AES)	1/7.5 to 1/10,000 (auto)
Digital Slow Shutter (DSS)	1/7.5 to 1/50 or 1/60 with up to 8x sensitivity boost in color or night mode
White Balance	Auto / ATW / Manual / One Push
Automatic Gain Control (AGC)	Auto
Back Light Compensation	On / Off
Wide Dynamic Range (WDR)	On / Off - 3 levels
Noise Reduction	3D
Tamper Detection	Yes
Privacy Zones	Yes
Video Motion Detection	Yes
Day / Night Mode	Yes
Mechanical IR Cut Filter	Yes
Signal to Noise Ratio (SNR)	±50 dB
Video	
Compression	Fully compliant multi-stream H.264 main/high profile + MJPEG
Maximum Performance	H.264 30/25 @ 1080p + 720p + D1 (NTSC/PAL)
Resolution Range	Scalable from D1 to FHD 1080p
Bandwidth	Configurable between 64Kbps and 20Mbps
Rate Control	CVBR
SD Card Recording ¹	microSDXC up to 64GB (Class 10)
IR Illuminator	
Distance	up to 30m (98 ft.)
Angle of Illumination	Full 60°
LED Type	high efficiency SMD
Peak Emission Wavelength (nm)	850
Network	
Network Protocols	TCP, UDP, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP, SMTP, SNMP, IGMP, 802.1X, QoS, IPv4, IPv6, SSL, LDAP
Ethernet	10/100, auto sensing, half / full duplex (RJ45)
Remote Configuration	via web browser or supported video management software
Firmware Upgrade	Flash memory for upgrade of camera firmware over the network
Supported Web Browser	Internet Explorer 10+
Security	User account with password protection and IP filter
Audio	
Input	CB-3102-11-I: G.711, AAC 8KHz 16bit
Alarm	
Input	CB-3102-11-I: 1 dry alarm contact
Physical	
Enclosure	Indoor/Outdoor: IK7 rated vandal IP67
Dimensions	CB-3102-01-I: 180 x 86 x 80 mm (7.08 x 3.39 x 3.15 in.) CB-3102-11-I: 215 x 86 x 80 mm (8.48 x 3.39 x 3.15 in.)
Unit Weight	CB-3102-01-I: 0.45kg (0.98 lbs.) CB-3102-11-I: 0.675kg (1.49 lbs.)
Mechanical	
Pan / Tilt / Rotate	360, ±80° and 360
Electrical	
Input Voltage	802.3af PoE
Power Consumption	CB-3102-01-I: 5W / 9W with heater and IR CB-3102-11-I: 8W / 12W with heater and IR
Power Connector	PoE
Environmental	
Operating Temperature ²	-40°C to 50°C (-40°F to 122°F)
Storage Temperature	-40°C to 60°C (-40°F to 140°F)
Humidity	90% (non-condensing)

¹ Excluding countries where disallowed

² Startup temperature -10°C/12°F

Camera Ordering Information

Type	Series	Camera Resolution	Lens Options	Environmental	IR Illuminator
CB	31	02	x	1	I
Bullet Camera	31 = Ariel Gen II	02 = 1080p FHD	0 = 2.8mm 1 = 3-10mm	1 = IP67 Vandal with Heater	I = 60° Illuminator

Accessories

A complete list of mounts, brackets, pole mounts and recess kits for cameras can be found in the FLIR Price List and Camera Accessory Guide.

Warranty & Regulatory	
Warranty	According to FLIR RMA Policy and Process Notice document
USA	UL, FCC Part 15 (subpart B, class A)
International	CE marked, EN55022-1998 class A, EN55024, RoHS



CORPORATE HEADQUARTERS

FLIR Systems, Inc.
27700 SW Parkway Ave.
Wilsonville, OR 97070
PH: +1 877.773.3547

FLIR Systems, Inc.
6769 Hollister Ave,
Goleta, CA 93117

FLIR Systems, Inc.
65 Challenger Rd
Ridgefield Pk., NJ 07660
PH: +1 201.368.9700

CANADA

FLIR Systems - Canada
250 Royal Crest Court
Markham, Ontario,
Canada L3R 3S1
PH: +1 888.425.6739

www.flir.com
NASDAQ: FLIR

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2016 FLIR Systems, Inc. All rights reserved. 05/2016