



Technical data

Format	Product	Focal length in mm	Zoom ratio	Iris range	Angle of view (HxV)	Iris control	M.O.D. in m	Mount	Weight in kg
--------	---------	--------------------	------------	------------	---------------------	--------------	-------------	-------	--------------

60x telezoom lenses

2 megapixel Full HD resolution – motor drive zoom and focus, built-in 2x extender, built-in filter wheel (ND 1/8, ND 1/64, visible light cut and clear)

1/1.8"	D60x16.7SR4*	 16.7~1000 (1x) 33.4~2000 (2x)	60	F3.5~F16 (1x) F7~F32 (2x)	20° 51' x 15° 54' 0° 22' x 0° 17'	Auto Iris (DC) or remote	5	C	6.3
2/3"	D60x20SR4*	 20~1200 (1x) 40.1~2400 (2x)	60	F3.5~F19.2 (1x) F8.4~F38.4 (2x)	23° 03' x 17° 67' 0° 42' x 0° 32'	Auto Iris (DC) or remote	5	C	6.6

*DE-V21 Zoom and focus preset function
 *GE-V21 Zoom and focus preset function, IR cut filter
 *DE-ZP1A PC control via RS232C, autofocus function (one shot)
 *FE-ZP1C PC control via RS232C, autofocus function (one shot), optical image stabilisation

32x zoom lenses

2 megapixel Full HD resolution – motor drive zoom and focus with preset function, PC control possible via RS232C interface, support of Pelco-D, built-in fog filter

1/1.8"	FD32x12.5SR4A-CV1	 12.5~400	32	F3.1~F16	30° 54' x 23° 32' 01° 02' x 0° 46'	Switchable iris (Video or DC) or remote	3	C	2.8
2/3"	FH32x15.6SR4A-CV1	 15.6~500	32	F3.9~F16	30° 56' x 23° 36' 01° 02' x 0° 46'	Switchable iris (Video or DC) or remote	3	C	2.9

32x zoom lenses

1.3 megapixel resolution – motor drive for zoom and focus with preset function

1/2"	D32x10HR4D-VX1	 10~320	32	F2.5~T1500	35° 26' x 26° 59' 01° 09' x 0° 52'	Switchable iris (Video or DC) or remote	3	C	2.5
	D32x15.6HR4D-VX1	 15.6~500	32	F3.9~T1500	22° 44' x 17° 11' 0° 45' x 0° 34'	Switchable iris (Video or DC) or remote	3	C	2.7

Remak: these products are discontinued. Remaining stock is available, status May 2016

Specifications are subject to change without notice. 05/16

FUJIFILM

FUJIFILM Europe GmbH

Heesenstr. 31, 40549 Düsseldorf, Germany
 Tel.: +49 211-50 89 0, Fax: +49 211-50 89 344
www.fujifilm.eu