



## C-View

## DATA SHEET

### Fully functional PTZ Domes



The new C-View range of Vandal resistant Day/Night PTZ domes are sealed to IP67 and designed to be installed in harsh and challenging environments. The domes are designed to be operated and installed easily and quickly. The PTZ domes can be used either externally or internally.

The fully functional PTZ domes have been constructed from vandal resistant die-cast aluminium and are powder coated to protect from scratching, oxidation, or attacks from solvents.

Various brackets allow the domes to be either pendant, wall or swan mounted for indoor and outdoor use.

The dome has 32 presets and also feature preset and mimic tours. Additional features include privacy zones and an extensive range of built in protocols. Remote dome configuration is also possible.

### Key Features

- Day / Night
- High Resolution
- Vandal resistant
- Optically distortion free polycarbonate bubble
- 36x optical zoom
- 32 presets
- 16 preset tours (8 slow & 8 fast)
- 4 x mimic tours at 1 minute intervals
- RS485 / Coax / UTP telemetry control
- 15 user definable privacy zones
- Electronic flip
- Upload / Download of camera settings
- 360 degree continuous rotation
- Remote reset and configuration
- Variable pan speed of 0.01° - 360 ° / sec
- Variable tilt speed of 0.01° - 200 ° / sec
- Flexible mounting options

### Ordering Information

C-DN2X36YPT-W	1/4" Day/Night PTZ camera, 36:1, Wide Dynamic, White
C-DN2X36YPT-B	1/4" Day/Night PTZ camera, 36:1, Wide Dynamic, Black
C-DN2X36P-W	1/4" Day/Night PTZ camera, 36:1, White
C-DN2X36P-B	1/4" Day/Night PTZ camera, 36:1, Black
C-APM-W	Pole mount swan neck dome adaptor, c/w lanyard clip (swan neck). White
C-APM-B	Pole mount swan neck dome adaptor, c/w lanyard clip (swan neck), Black
C-AWM-W	Wall mount brackets, c/w lanyard clip, White
C-AWM-B	Wall mount brackets, c/w lanyard clip, Black
C-APPM-W	Pendant Pole mount bracket, White
C-APPM-B	Pendant Pole mount bracket, Black
C-ACMA-W	Corner Adaptor, White to suit C-AWM-W
C-ACMA-B	Corner Adaptor, Black to suit C-AWM-B





## C-View

# DATA SHEET

Fully functional PTZ Domes

### Technical Specification

MODEL	C-DN2X36YPT	C-DN2X36P
Video System	PAL	
Video Output	1.0 V (p-p) / 75	
Image Sensor	1/4" IT CCD	
Horizontal Resolution	530 TVL	520 TVL
Minimum Illumination	1/60s 1.4 lux; 1/4 s 0.1 lux	1.0 lux (colour) F1.6; 0.05 lux (B/W) F1.6; 0.015 lux (B/W) F1.6 32x
Horizontal Viewing Angle	1.7 degrees to 57.8 degrees	1.7 degrees to 57.8 degrees
Effective Elements	752 (H) x 582 (V)	
Zoom	36 x optical, 16 x digital	
Lens	3.4 - 122.4 mm (F1.6-F4.5)	3.4 - 122.4 mm (F1.6-F4.5)
S/N Ratio	>50 dB	
Sync System	INT. /L.L.	
Gamma Characteristic	0.45	
White Balance	AWB, indoor, outdoor, manual	
Backlight Compensation	ON / OFF	
Pan Rotation	Continuous	
Tilt Rotation	180°	
Tilt Speed	0.01° - 200° / sec	
Pan speed	0.01° - 360° / sec	
Pan Coverage	360 degrees (continuous rotation)	
IP Rating	IP 67	
Mount Type	Wall mount and ceiling mount	
Preset Accuracy	14 bit resolution encodes (0.1 degrees)	
Preset Positions	32	
Preset Tours	16	
Mimic Tours	4 x 1 mimic tours	
Video gain and lift	16 steps	
Preset Titling	Yes	
Privacy zones	24 positions, with separate algorithms to account for offset tilt of head unit or inverted operation (12 privacy zones if E-flip is enabled)	
Configuration Download/Upload	Yes	
Protocols	Pelco P, Pelco D, BBV coaxial, VTC, Sensormatic, Samsung SCC300, Kalatel, C-Dome, C-AllView, Overview RS485	
Controller Interface	RS-485 half duplex data communication Coaxial Telemetry Optional	
Alarm	Comprehensive alarm options with timed masking	
Real Time Clock	Yes	
IR Mode	Via External input IR Lamp Power Optional	
Mounting Options	Diagonal mount, (60 mm)	
Housing Colour	Black (RAL9011) or White (RAL9002)	
Power Supply	18-28 V AC / DC (PSU included)	
Vandal Resistant	Yes	
Operating Temperature	-20°C ~ +50°C, Relative humidity 90%	
Operating Voltage	24 V AC / DC	
Power Consumption Max	10W	
Dimensions	207 (D) x 250 (H) mm	
Weight	5.8 kg	

Features and specifications are subject to change for further improvement without any notice  
Note:

Some of the supported devices listed above are not manufactured by CBC (Europe). It is therefore possible that the protocols have been changed from the original manufacturer or are in different configurations from the units previously tested by CBC (Europe).

CBC (Europe) recommends that a compatibility bench test prior to installation of the complete system is carried out to ensure complete functional requirement. CBC (Europe) will not be liable for any installation costs or lost revenues in the event of any compatibility problems where they occur.

