


C-ML219VC

19" VGA/BNC TFT CCTV Monitor



The C-ML range of commercial LCD Monitors offers good picture quality and a sleek and pleasant design normally associated with higher end units. An impressive 800:1 contrast ratio and 1280 x 1024 resolution and response time of 6ms gives you the ultimate performance and delivers crisp clear images.

This range of monitors also feature analogue input VGA and S-Video capabilities providing various connection options. The slim design maximises desktop space and makes a perfect fit for almost any office or commercial application. The desk mount can be easily removed to allow the monitor to be fitted with any standard 100mm VESA accessories.

Key Features

- ▶ POS / ATM Terminals
- ▶ Wide viewing angle
- ▶ High contrast ratio
- ▶ Built in speaker
- ▶ Multi language OSD
- ▶ 3D comb filter High quality motion adaptive
- ▶ 4H comb filter adaptive for the best image quality
- ▶ 3D noise reduction
- ▶ 1280(H) x 1024(V) SXGA Resolution

V1.01

C-ML219VC

19" VGA/BNC TFT CCTV Monitor

Specifications

Description / Model	C-ML219VC
MONITOR SPECIFICATION	
Display Type	19" Active Matrix TFT LCD Module
Resolution	1280(H) x 1024(V) SXGA
Pixel Pitch	0.294 (H) x 0.294 (V)
Display area	376.32 (H) x 301.056 (V) mm
Contrast ratio	800:1
Brightness	300 Cd/m ²
Response time	6ms
Colours	16.7M
Video Synchronization	TTL Positive or Negative
Viewing Angle L/R	75°/75°
Viewing Angle U/D	75°/75°
Adjustable Colour Temperature	9300K / 6500K / 5800K / User
Aspect Ratio	4 : 3 Ratio
VGA Auto Frequency Correction	Yes
OSD Control	Contrast, Brightness, Clock, Phase, H-Position, V-Position, Language, Reset
OSD Language	English, French, German, Spanish, Italian, Chinese
INPUT INTERFACE	
Input /Output	VGA- D-SUB x 1, Video in BNC x 1, Video Out BNC x 1 (loop through), S-Video x 1
Audio	Audio in x 1, Audio Out x 1
Speaker	2.5W x 2, Multimedia Speakers (Right x 1 Left x 1)
PC Compatible Frequency	30-80KHz(H) / 50-75Hz(V) Max.1280 x 1024
Auto Sensing	NTSC / PAL
Termination	75 Ohms (Automatic termination)
NB. Specification subject to change without notification	

POWER	
Power	AC in x 1
Power Supply	12VDC, 4amp
Voltage	AC100 - 240V 50 / 60Hz
Power Consumption	< 40W
MECHANICAL	
Bezel Thickness	20mm
Vesa Standard Mount	100 x 100 mm
Stand Type	Desktop
Colour	Black
LCD Dimension (Without Base)	425 (W) x 345 (H) x 65 (D) mm
Packing Dimension	480 (W) x 500 (H) x 165 (D) mm
Accessories	Power Supply / Power Lead / VGA Cable / User's guide/ Audio cable
Weight	Net Weight: 5.5kgs,Gross Weight: 6.5kgs
Work Temperature / Humidity	Temperature: - 10 to 50 °C Humidity: 20 % - 70 %
Certificate	CE / FCC / ROHS
Warranty Period	3 Years



V1.01