

CHOV-II

Medium Housing

Stylish Enviromental housing that is designed to make the installation and servicing easier. Due to its side opening, the accessibility to the lens, camera and its connections is quicker.


The body is made of aluminium and the sunshield of ABS material. Its IP 66 weatheproof features makes the houing ideal for all weather condition.

The CHOV II can be supplied with a integrated self-parking wiper (optional). It is possible to have either a standard bracket or a cable managed bracket with the housing.

The CHOV II can accept Vari focal lenses, Fixed focus lenses and 6:1 zoom lenses.

Ordering Information:

CHOV II IP66 external Housing 230Vac Input
 CHOV II /12 IP66 external Housing 12Vdc Input
 CHOV II /24 IP66 external Housing 24Vac Input



Housing showing side opening with camera/lens (not included)

MODEL	CHOV-II
Water Resistance	IP66
Construction	Aluminium
Colour-Body	CBC Grey
Sun Shield	RAL 9002
Operating Temperature	-20°C ~ 50°C (with heater)
Heater Temperature On	< 15°C +/- 3°C
Temperature Off	> 22°C +/- 3°C
Heater Consumption	IN 12Vdc/24Vac, consumption 20W / IN 115/230Vac, consumption 40W 1200mA (12Vdc) / 600mA (24Vac / 180mA (230Vac)
Blower Temperature On	> 35°C +/- 3°C
Temperature Off	< 20°C +/- 3°C
	IN 12VDC or 24VAC or IN 100-240VAC, OUT12VDC (4W max)
Dimensions	
Internal (W x H) mm	100 x 70 (useable area)
External (W x H x L) mm	115 x 163 x 514
Weight	2.54Kg

KEY FEATURES:

- Easier installation (side opening)
- Indoor/Outdoor installation (IP66)
- Integrated wiper option
- Wall and ceiling mount options (internal and external)
- Different mounting options; standard bracket, cable management bracket or P&T

