



1080P AHD IR PTZ



Z8-P4NTAF66LAC

Features:

- 1/2.9" Progressive Scan CMOS
- 4.6~152mm Lens
- 33X Optical Zoom
- Full HD 1080P
- 3D DNR, dWDR
- IR Range 492'
- IP66, TVS4000V

Z8-P4NTAF66LAC

1080P AHD IR PTZ

■ Specifications

Model	Z8-P4NTAF66LAC
Image Sensor	1 / 2.9" Sony Progressive Scan CMOS
Signal System	NTSC / PAL
Minimum Illumination	Color 0.1Lux@(F1.2,AGC ON) ; B/W:0Lux@(IR LED ON)
Day / Night Performance	True Day / Night (ICR)
Shutter Speed	NTSC 1/60-1/60000 ; PAL 1/50-1/50000s
Auto Iris	Auto
Wide Dynamic Range	Digital WDR
Digital Noise Reduction	2D / 3D
S/N Ratio	>58dB
Lens	33X, 4.6mm~152mm Lens
Field of View	55.2°~3.2°
IR LED	12 IR LEDs (492' Range)
Up the Coax	Yes
Alarm I/O	4ch Alarm In, 1ch Alarm Out
Heater	Yes
Mirror	Yes
BLC	Yes
HLC	Yes
Motion Detection	N/A
Video Output	AHD
Pan / Tilt	Pan continuously 360°, Tilt 0~90° with auto-flip
Pan / Tilt Speed	Pan: 0.1~200° /s, Tilt: 0.1~180° /s
Preset / Tour / Scan / Pattern	128 / 4 / 4 / 4
Max. Resolution	1920(H) x 1080(V)
Power Supply	24VDC / 2.5A
Power Consumption	MAX 60W
Operating Temperature	Starting Temperature -14°F ~ 131°F (-10°C ~ 55°C) Working Temperature -22°F ~ 140°F (-30°C ~ 60°C)
Installation	Wall mount, Pendant mount
Dimensions	8.9" (Ø) x 13.2" / 226mm (Ø) x 336.5mm
Weight	15.2lbs / 6.9Kg
Certifications	CE, FCC, IP66, TVS4000V

All specifications are subject to change without notice.