

## TECHNICAL DATA SHEET

# GTA004

## Active Baluns



## KEY FEATURES

Genie's "Smart Cabling" Active Baluns are designed for use with Category 5e Unshielded Twisted Pair (UTP) cable. Each Transmitter and Receiver is supplied with a DC12V Power supply as standard and can transmit and receive full motion composite video signals up to 900 metres in Colour and 1800 metres in Monochrome.

- Transmits Full Motion Colour or Monochrome Video Signal
- Monochrome video transmission up to 1800m or up to 900m in Colour
- Built in Transient Protection and Ground Lifting
- Modular Design
- Can be "Daisy Chained" Together by Removing the End Caps
- Frequency Compensation, Low, Medium, High
- DC12V Power to Camera From – Maximum 300mA
- Red LED: Power On / Off Indication
- Can Be "Daisy Chained" Together by Removing the End Caps
- Brightness Control
- Ten-position Distance Range Switch to Adjust Signal Strength
- DC12V Power Supplies Included, 500mA

## TECHNICAL DATA SHEET

### TECHNICAL SPECIFICATION

Model Number	GTA004
Video Input	1 Vp-p75 Ohm (BNCCconnector)
Power	DC 12 V
DC Output for Camera	40mA (Max)
Power Consumption	Cat 5eCable 4-pair (24AWG)
Dimensions (W x H x D)	49mm x 42mm x 45mm

Features and specification are subject to change for further improvement without any notice.