

## TECHNICAL DATA SHEET

# LM-5.6

## 5.6" TFT LCD Monitor



### KEY FEATURES

- 2 x Composite Input
- Active Matrix Technology
- 2 AV (Mono) Inputs & 1 Audio (Mono) Output Jack
- 15ms Response Time
- Video 1 and Video 2
- NTSC/PAL Auto Switching
- On-Screen Display Menu
- Built-in Rear Speakers
- Remote Controller Included
- DC 12V

## TECHNICAL DATA SHEET

### TECHNICAL SPECIFICATION

Model Number	LM-5.6
Brightness	330cd/m <sup>2</sup>
Resolution (H x V)	960 x 234
Contrast Ratio	150:1
Aspect Ratio	4:3
Pixel Pitch	0.118 x 0.362
Number of Pixels	112,320 Pixels
Viewing Angle (H x V)	90° x 40°
Display Size (Diagonal)	5.6-Inch
Response Time	15ms
Video System	NTSC / PAL Auto Switching
LCD Backlighting	ColdCathode Fluorescent Light (CCFL)
Video	2 x Composite Video
Audio	2 x Input via RCA Jack
Video Input	1V p-p 75 Ohm
Backlight Life	20,000 hrs
Power Supply	DC10 - 36V
Power Consumption	550mA @ DC 12V
Operating Conditions	Operating Temperature: -10°C ~ 70°C, Storage Temperature: -30°C ~ 80°C
Dimensions (W x H x D)	155 x 105 x 25 mm
Weight	1kg (With Stand)

Features and specification are subject to change for further improvement without any notice.