

TECHNICAL DATA SHEET

Rapport III PRO

Multi-Functional CCTV Tester



KEY FEATURES

- All-in-One Multifunctional CCTV Tester
- CCTV Test Monitor
- Video Level & Sync Measurement
- Video Signal Generator
- Multimeter
- PTZ Controller
- PTZ Protocol Analyser
- UTP Cable Tester
- Faster Charge Time
- Longer Battery Life
- Built in DVR

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	Rapport III
TFT LCD Monitor Screen	3.5
Display Resolution (W x H)	960 x 240
Active Area (W x H)	72 x 50.544
Dot Pitch (W x H)	0.150 x 0.216
Colour Configuration	R.G.B. Delta
Viewing Angle	Top: 15°, Bottom: 35°, Left & Right: 40
Contrast Ratio	Min: 100, Typical: 120
Video Input / Output	IVp-p 10%, 75 Ohm
Power	DV 12V
Power Consumption	190mA° 20mA
Operating Conditions	Temperature: 0°C ~ 50°C, Humidity: 90% RH
Dimensions (W x H x D)	83 x 60.5 x 3.3 mm
Weight	40g
Input Voltage	12V± 10% Above 1.2A
Battery	Lithium Polymer Battery (Inner Packaging)
Charging Time	Approximately 5 Hours
Operational Time	Approximately 6 Hours (*based on average usage)
Signal System	NTSC / PAL
Video Level	1Vp-p 140 IRE
Protocol	Multiple
Transmission	2400bps ~ 115.2Kbps
Transmission Mode	RS-422 / RS-485
DVR	YES (Built-in SD Card Storage)
Tests	Continuity/Crossed Cable and Breaks or Short Circuits
AC Voltage	Max. 300V
DV Voltage	Max. 300V
Resistance	Max. 40 M Ohm
Continuity	Beeper is Activated when the Resistance is Below 20 Ohm
Dimensions (W x H x D)	88 x 126 x 40 mm
Weight	380g

Features and specification are subject to change for further improvement without any notice.