

TECHNICAL DATA SHEET

TPH-2000

Mid-Size Camera Housing



KEY FEATURES

- Pressure Die-Cast Aluminium Alloy Construction
- Fully Cable Managed Bracket
- Adjustable Sliding Camera Tray
- Sealed Cable Entry Glands
- Additional Fixing Holes on Underside for IR Lighting
- Removable Top Cover for Easy Access
- Includes Dual 24V AC/12V DC Heater
- IP-67 Rated

TECHNICAL DATA SHEET

TECHNICAL SPECIFICATION

Model Number	TPH-2000
External Dimensions (W x H x D)	127 x 124 x 390 mm
Internal Dimensions (W x H x D)	90 x 70 x 240 mm
Window (W x H x D)	82 x 68 x 4 mm
Finish	Light Ivory PowderCoat & Stove Finished
Cable Inlet	2 x PGA 13.5 (Ø 5 to 8.8mm)
Heater	Dual 24V AC or 12V DC Heater Switches On at 18°C & Off at 28°C
Heater Current	1.12A (DC 12V) / 760mA (AC 24V)
IP Rating	IP67
Power Supply	DC 12V / AC 24V
Weight	Housing 1.9Kg, Bracket 0.66Kg

Features and specification are subject to change for further improvement without any notice.