

Geoffrey

Advanced Reader PR400 Series™



Reader (PR400)

The New Geoffrey™ PR400 Series Proximity & Smart reader range takes RF/ID technology to the ultimate in sophistication, customer acceptance, and cost effectiveness. The PR400 readers are quick and easy to install and have been designed for the most demanding access control applications. One of the most unique features of the PR400 series is the ability to offer custom branded technology & housings with company names, logos and colors. A choice of body and cap colors is also available to suit corporate styles.

FEATURES

- **Cards and Tags**
A wide range of identity cards and key fobs are available to suit virtually every application. Standard ISO style plastic cards, with or without magnetic stripe, can be surface printed using standard PVC card printers
- **Environmental**
The PR400 series is suitable for both indoor and outdoor use. The readers will operate reliably in harsh environments with temperature -20°C to +60°C

- **Quick and Easy to Install**
Surface fixing design with stainless steel fixings supplied. May be fixed flush to metal surfaces with no significant loss of range. Specially moulded covers are provided to hide the fixing screws
- **Flexible Connection**
Two visual indicators and an integral beeper allow for various connection combinations. The beeper and one LED can be controlled externally giving complete flexibility for control applications
- **Multi Technology Cards**
ISO PVC cards are available with a Hi-Co magnetic stripe plus smart chip for multi-function applications. Also allows backward compatibility with installed magnetic stripe readers
- **Input power**
5 –16 VDC
- **Current**
120 mA typical
- **Data Voltage**
Rest >4VDC, Active <1VDC
- **Data Output**
Wiegand Format
Magnetic Stripe
Customized
- **Indication**
Red LED - power
Green LED - card read
Buzzer - audible indicator
- **Environmental**
Operating Temp-20°C to +60°C
Humidity: 100% RHNC

SPECIFICATION

- **Read Range**
ProxCard® II Card – 18 cm
ISOProx® Card - 12 cm
ProxKey™ Keyfob - 4 cm ProxCard® Plus Card® - 6 cm
Smart Mifare® Card – 3 cm
Smart LEGIC® Card – 5 cm
- **Mechanical (Housing)**
Moulded polycarbonate with fully encapsulated Electronics
Size: 108mm×52mm×22mm
Weight: 115g nominal
Mounting: 2X M3.5 screws (supplied)
- **Connection**
 1. 5 to 16 VDC
 2. Clock / Data 1
 3. Data / Data 0
 4. Green LED
 5. Red LED
 6. Card present
 7. Supply 0V

Part Number

- GPR402-G34**
Geoffrey™ Proximity Formats
- GPR430**
HID® Proximity Formats
- GPR470**
Smart LEGIC® Contactless Technology
- GPR480**
Smart Mifare® Contactless Technology

Geoffrey

Geoffrey Industries (UK) Ltd
Amberwell House, Pottersheath Rd
Welwyn, Hertfordshire, AL6 9SY
Phone +44 (0) 1438 817000
Facsimile +44 (0) 1438 814344
e-mail: info@geoffrey.co.uk
Web Site, www.geoffrey.co.uk