

## Colour monitor series GCVM

... the new series of Colour Monitors



- Very high resolution
- Universal power supply, 90 - 256 VAC
- 2 x switchable video inputs with loop-through
- Additional, S-video input with loop-through
- Automatic PAL/NTSC signal selection
- Metal case

Technical data			
	GCVM-14H/R	GCVM-17H/R	GCVM-21
Video standard	CCIR/PAL, EIA/NTSC, automatic selection		
Screen size	14" (35 cm)	17" (43 cm)	21" (53.3 cm)
Horizontal resolution	> 600TVL	> 600TVL	> 520TVL
Recommended viewing distance	1 to 1.6 m	1.3 to 1.6 m	1.6 to 2.4 m
Video inputs			
- Composite	2 inputs, 1.0 Vpp 75 Ohm/Hi-Z, loop-through 2 x BNC each		
- S-video	1 input, Y = 1.0 Vpp C = 0.3 Vpp 75 Ohm/Hi-Z, loop-through 2 x mini-DIN		
Audio	1 input, 150 mV, Hi-Z, 2 x RCA (phono) jack, loop-through		
Bandwidth	8 MHz		
Gain	30 dB		
Power supply	90 - 256 VAC (50Hz)		
Power consumption	57 W	50 W	75 W
Operating temperature	-10°C to +50°C		
Dimensions	375 x 362 x 321 mm (w x h x d)	475 x 420 x 422 mm (w x h x d)	501 x 490 x 453 mm (w x h x d)
Weight	15 kg	23 kg	32 kg
Colour	Anthracite		
Case material	Metal, front plastics		
Certifications	UL, CE, CSA, FDA, FCC, CUL, TÜV		
Order no.	<b>5.11500</b>	<b>5.11510</b>	<b>5.11520</b>

7.75211 V 1.0 09/03

Technical alterations reserved

[www.geutebrueck.de](http://www.geutebrueck.de)

**GEUTEBRÜCK GmbH**  
 Im Nassen 7-9 · D-53578 Windhagen  
 Tel. +49 (0)2645 137-0 · Fax-999 · E-mail: [info@geutebrueck.de](mailto:info@geutebrueck.de)