

# Lenses

Lenses with variable focal lengths, for a wide-range of applications



## Product information

- | MPZ4,0-12,0MI
- | MPZ4,0-12,0AI-DC
- | MPZ4,0-12,0AI-DC
- | MPZ5,0-50,0AI-DC-DN
- | MPZ3,5-10,0MI-DN
- | MPZ9,0-20,0MI-DN

## Technical data

|         |                     |   |
|---------|---------------------|---|
| 5.07905 | MPZ4,0-12,0MI       | <p>Manual aspherical megapixel vario focal lens for use under normal lighting conditions.<br/>           Focal length: 4.0 - 12.0 mm<br/>           F-stop: F1.4 - C<br/>           Format: 1/2"<br/>           Mount type: C-Mount<br/>           1/2" angle of view H: 93.9°-31.4° V: 68.8°-23.6°<br/>           1/3" angle of view H: 68.8°-23.6° V: 51.0°-17.7°<br/>           Minimum object distance: 30 cm<br/>           Dimensions in mm (W x H x D): 40.0 x 40.0 x 54.5<br/>           Weight: 59 g<br/>           Brand: Tamron</p>  |
| 5.07906 | MPZ4,0-12,0AI-DC    | <p>Aspherical megapixel vario focal lens with direct controlled iris.<br/>           Focal length: 4.0 - 12.0 mm<br/>           F-stop: F1.4 - 360<br/>           Format: 1/2"<br/>           Mount type: C-Mount<br/>           1/2" angle of view H: 93.9°-31.4° V: 68.8°-23.6°<br/>           1/3" angle of view H: 68.8°-23.6° V: 51.0°-17.7°<br/>           Minimum object distance: 30 cm<br/>           Dimensions in mm (W x H x D): 40.0 x 58.1 x 54.5<br/>           Weight: 69 g<br/>           Brand: Tamron</p>  |
| 5.07908 | MPZ5,0-50,0AI-DC-DN | <p>Megapixel vario focal lens with direct controlled iris for use with day/night cameras (no IR focus shift).<br/>           Recommended for resolutions of up to 1.3 Megapixel.<br/>           Focal length: 5.0 - 50.0 mm<br/>           F-stop: F1.6 - 360<br/>           Format: 1/3"<br/>           Mount type: CS-Mount<br/>           1/3" angle of view H: 51.2°-5.3° V: 39.4°-4.1°<br/>           Minimum object distance: 30 cm<br/>           Dimensions in mm (W x H x D): 40.5 x 55.2 x 64<br/>           Weight: 85 g<br/>           Brand: Fujinon</p>   |
| 5.07920 | MPZ3,5-10,0MI-DN    | <p>Manual aspherical megapixel vario focal lens for use with day/night cameras (no IR focus shift).<br/>           Recommended for resolutions of up to 5 Megapixel.<br/>           Focal length: 3.5 - 10.0 mm<br/>           F-stop: F1.6 - 22<br/>           Format: 1/2"<br/>           Mount type: CS-Mount<br/>           1/2" angle of view H: 84.9°-35.5° V: 68.9°-27.0°<br/>           1/3" angle of view H: 68.9°-27.0° V: 54.4°-20.4°<br/>           Minimum object distance: 20 cm<br/>           Dimensions in mm (W x H x D): 36.5 x 36.5 x 58.2<br/>           Weight: 99 g<br/>           Brand: Kowa</p> |
| 5.07922 | MPZ9,0-20,0MI-DN    | <p>Manual aspherical megapixel vario focal lens for use with day/night cameras (no IR focus shift).<br/>           Recommended for resolutions of up to 5 Megapixel.<br/>           Focal length: 9.0 - 20.0 mm<br/>           F-stop: F1.6 - 22<br/>           Format: 1/2"<br/>           Mount type: CS-Mount<br/>           1/2" angle of view H: 39.1°-18.2° V: 29.9°-13.7°<br/>           1/3" angle of view H: 29.9°-13.7° V: 22.6°-10.3°<br/>           Minimum object distance: 50 cm<br/>           Dimensions in mm (W x H x D): 36.5 x 36.5 x 62.0<br/>           Weight: 95 g<br/>           Brand: Kowa</p> |