

Lenses

Motor zoom lenses for a wide-range of applications



Product information

- | MZ8,0-48,0AI-DC-PT
- | MZ8/120AI-DC-PT
- | MZ8/48AI-DC-IR-PT

Technical data

5.09210	MZ8,0-48,0AI-DC-PT	<p>Motor zoom lens with direct controlled iris and potentiometer for pre-positioning. Focal length: 8.0 - 48.0 mm F-stop: F1.2 - 560 Format: 1/2" Mount type: C-Mount 1/2" angle of view H: 44.6°-8.0° V: 33.5°-6.0° 1/3" angle of view H: 33.5°-6.1° V: 25.1°-4.6° Minimum object distance: 120 cm Dimensions in mm (W x H x D): 66.0 x 73.5 x 97.0 Weight: 450 g Note: Suitable for all applications with or without fixed positions (presets).</p>
5.07630	MZ8/120AI-DC-PT	<p>Motor zoom lens with direct controlled iris and potentiometer for pre-positioning. Please note: Because of the lens dimensions we only can recommend to install the lens into the weatherproof housing type WSG-304X. Focal length: 8.0 - 120.0 mm F-stop: F1.8 - 360 Format: 1/2" Mount type: C-Mount 1/2" angle of view H: 44.0°-3.1° V: 33.0°-2.3° 1/3" angle of view H: 30.0°-2.1° V: 22.5°-1.6° Minimum object distance: 120 cm Dimensions in mm (W x H x D): 69.0 x 80.0 x 128.0</p>
5.07572	MZ8/48AI-DC-IR-PT	<p>Motorised zoom IR-coated lens, (AI-DC) focal length f 8.0 - 48 mm (6 x) high luminous efficacy iris control via video signal with remote indication potentiometer for pre-positioning direct control iris via connected camera motorised focal length and focus f-Stop F 1.0 - 720 IR-optimized at 850 nm C-Mount lens connection, 1/2" format brand: Pentax suitable for B/W-IR cameras!</p>