

QUAD-4/Color

Colour quad display with 4 inputs



- 2-times digital zoom of free definable picture segments while recording and playback
- Additional analog video recorder input and output
- Easy programming via OSD menus
- High resolution of 720 x 576 pixel

Technical data	
Video standard	CCIR / PAL, EIA / NTSC
Resolution	720 (H) x 576 (V) pixel (PAL), 720 (H) x 480 (V) pixel (NTSC)
Picture rate	50 fields / s (PAL), 60 fields / s (NTSC)
Video inputs	4 x composite (BNC-sockets), 75 Ohm or high-impedance, 4 x loop through sockets (with automatic termination)
Recorder input	1 x composite (BNC-socket), 75 Ohm
Monitor outputs	2 x composite (BNC-sockets), 75 Ohm
Recorder output	1 x composite (BNC-socket), 75 Ohm
Control	
Alarm inputs	4 x potential free inputs (NO/NC)
Alarm outputs	1 x contact (TTL level) activ HIGH and relais NO/NC
General	
OSD menu language	English
Operating voltage	12 VDC, power supply unit included in delivery
Power consumption	approx. 7,5 W
Temperature range	0°C - 45°C
Dimensions in mm	240 x 44 x 170 (W x H x D), w/o connectors and floor stand
Weight	approx. 2 kg
Order number	5.27890

Technical alterations reserved.