Weather- and dustproof housings

Series 500



Product information

Compact weather- and dustproof housing for 230 VAC cameras and low voltage cameras

- Also available with concealed cable access
- Aluminium case with V2A stainless-steel screws
- Internal camera mounting-height adjustment
- 3 x cable glands
- Temperature regulation via PTC heating element and additional safety thermostat
- VDE approved construction
- IP-66 protection rating
- TÜV approved safety (German safety standards authority)



Technical data

	WSG-501/3	WSG-521/3
Description	Weatherproof housing with sun-shield, self-regulating heater and safety thermostat	
Concealed cable access	NO	YES
Finish	RAL 7032	
Case	Aluminium	
Heater supply	230 VAC	
Cable access	3 x PG-9 cable glands	Concealed access
Dimensions	Approx. 105 x 86 x 350 mm	
Usable internal size	320 mm	
Protection ranking	IP-66	
Weight	3.7 kg (incl. WK-500)	4.7 kg (incl. bracket)
Order No.	5.15780	5.15770
Accessories		
Туре	WK-500	MAK-W
Description	Adjustable wall-mounting bracket with locking-screw, RAL 7032 (pebble grey)	Mast adapter for lateral attachment of weather proof housing (WSG-421; WSG-521) to camera mast, material: high-tensile steel, fastening: stainless-steel bands
Order No.	5.18690	5.18371