Weather- and dustproof housings Series 500



Product information

Compact weather- and dustproof housing for 230 VAC cameras and low voltage cameras

- Also available with concealed cable access
- Aluminium case with V2A stainless-steel screws
- Internal camera mounting-height adjustment
- 3 x cable glands
- Temperature regulation via PTC heating element and additional safety thermostat
- VDE approved construction
- IP-66 protection rating
- TÜV approved safety (German safety standards authority)



Technical data

| | WSG-501/3 | WSG-521/3 |
|------------------------|--|--|
| Description | Weatherproof housing with sun-shield, self-regulating heater and safety thermostat | |
| Concealed cable access | NO | YES |
| Finish | RAL 7032 | |
| Case | Aluminium | |
| Heater supply | 230 VAC | |
| Cable access | 3 x PG-9 cable glands | Concealed access |
| Dimensions | Approx. 105 x 86 x 350 mm | |
| Usable internal size | 320 mm | |
| Protection ranking | IP-66 | |
| Weight | 3.7 kg (incl. WK-500) | 4.7 kg (incl. bracket) |
| Order No. | 5.15780 | 5.15770 |
| Accessories | | |
| Туре | WK-500 | MAK-W |
| Description | Adjustable wall-mounting bracket with locking-screw, RAL 7032 (pebble grey) | Mast adapter for lateral attachment of weather proof housing (WSG-421; WSG-521) to camera mast, material: high-tensile steel, fastening: stainless-steel bands |
| Order No. | 5.18690 | 5.18371 |