


# PWR-24AC-4-4UL



4 Camera 24VAC 4Amp Power Supply



The PWR-24AC-4-4UL is a UL listed CCTV power center engineered to manage remote camera and accessory power requirements. The PWR-24AC-4-4UL distribution module is designed with 4 individually fused outputs for powering up to 4 CCTV cameras and accessories. It will provide 24Volts AC via distribution to four fused outputs with a total of 4.0 Amps continuous supply current. The PWR-24AC-4-4UL power center is housed in a premium heavy gauge metal enclosure.

## Key Features

- Convenient screw and terminal and fuse access
- AC power LED indicator
- Includes transformer and spare fuses
- Multiple knockouts to accommodate various wiring configurations
- Uses easy to find automotive style fuses

## Technical Specifications

### PWR-24AC-4-4UL

#### FEATURES

- Convenient screw and terminal and fuse access
- Separation panel between transformers and output access
- AC power LED indicator
- Power ON/OFF switch
- Individual LED's for each fused output
- Lockable heavy gauge metal enclosure
- Double coated polyurethane finish
- Multiple knockouts to accommodate various wiring configurations
- Uses easy to find automotive style fuses
- Includes transformer and spare fuses

#### SPECIFICATIONS

Input	115VAC 50/60 HZ; 0.9 Amps
Output	fuses are rated at 3 Amps
Four 24VAC individually fused outputs	
Fuse	5 Amps
4 Amps 100 VA supply current at 70°F	
Unit maintains camera synchronization	
Transformer	110VAC/24VAC, 100VA
Enclosure Dimensions	254 x 228.6 x 114.3mm (10" x 9" x 4.5")
UL listed	

## Dimensions

Unit : mm (inch)

