

# Super High-Resolution DayNight WDR Camera

## SCC-B2335/B2035

NEW



### Features

- 1/3" SONY 410K/470K Pixels Super-HAD PS CCD
- High Resolution : 600 TV Lines
- Min. illumination  
0.0002Lux (F1.2, 15 IRE, Sens-Up 512x, Color)  
0.00002Lux (F1.2, 15 IRE, Sens-Up 512x, B/W)
- Internal/Line-lock (Phase Control) Function
- ALC(Video/DC) / ELC • Wide Dynamic Range (WDR)
- Virtual Progressive Scan (VPS)
- Day/Night Function (ICR), Sens-Up Function (512x)
- Motion Adaptive Digital Noise Reduction (3D+2D)
- Back Light Compensation (Area Setting)
- Advanced Motion Detection Function • eXtended Dynamic Range (XDR)
- Privacy Mask Function (Polygonal Mosaic)
- High Shutter Speed Control by External Trigger
- DIS (Digital Image Stabilization)
- CCVC (Camera Control Via Coaxial cable, Controller: SCX-RD100)
- RS-485(Half) Control (Multi-Protocol support)
- Multi-Language OSD support
- Intelligent Video (Moved / Fixed / Fence / Area / Tracking)
- C/CS Lens Mount Compatible
- SCC-B2335 : DC1.2V & AC24V 60Hz(50Hz)  
SCC-B2035 : AC220V(50Hz)

### Specifications

Model	SCC-B2335N	SCC-B2035P/B2335P
Camera Type	Color/BW	
Image	Device	
	Pixels	Effective
Scanning	System	
	Horizontal	Internal Mode
	Frequency	Line-lock Mode
	Vertical	Internal Mode
	Frequency	Line-lock Mode
Resolution	Horizontal	
Min. Scene Illumination	Color	Sens-up off
		Sens-up
	B/W	Sens-up off
		Sens-up
Functions	Number of Privacy Zone	
	Day/Night	
	Motion Detection	
	D-Zoom	
	High Speed Shutter	
	Sens Up / BLC / AGC	
	ELC / Line Lock	
	Camera ID / White Balance	
	eXtended Dynamic Range	
	Digital Noise Reduction	
	Digital Image Stabilization	
	Intelligent Video / PIP	
	Wide Dynamic Range	
	Virtual Progressive Scan	
	Etc. Function	
Video Output	VBS 1.0Vp-p	VBS 1.0VpN/Ap
S/N Ratio	S/N Ratio	
Lens	Lens Drive Type	MANUAL/AI(VIDEO/DC)
	Mount Type	CS/C
OSD		
Alarm	Output	1 ea
Remote Control	CCVC	Yes (with SCX-RD100)
	RS485	Yes (Multi Protocol, 8ea)
Environmental Conditions	Operating Temperature	Absolute : -20°C ~ +60°C / Sustained : -10°C ~ +50°C
	Operating Humidity	Less than 90%
Power	Power Requirement	24 VAC ±10%/12 VDC ±10% SCC-B2335P:24VAC ±10%/12 VDC ±10% SCC-B2035P:AC220V~240V(50Hz±0.3Hz)
	LED Indicator	Yes
Physical Specification	Dimensions (WxHxD)	64 x 58 x 109.2 mm SCC-B2335P:64x58x109.2 mm SCC-B2035P:64x58x129.2 mm
	Weight	305 g SCC-B2335P:305g/SCC-B2035P:395g
	Color	Body
		Silver

### Dimensions (unit:mm)

