

Super High-Resolution DayNight Anti-Vandal Dome Camera

SCC-B5396/B5398 NEW



Features

- 1/3" SONY 410K/470K Pixels Super-HAD IT CCD
- High Resolution : 600 TV Lines
- Min. illumination 0.00023Lux (F1.2, 15 IRE, Sens-Up 512x)
- SCC-B5396 : f=2.5~6 mm, Auto Iris Lens
SCC-B5398 : f=2.8~11 mm, Auto Iris Lens
- Internal/Line-lock (Phase Control) Function
- Day/Night Function (Soft), Sens-Up Function (512x)
- Motion Adaptive Digital Noise Reduction (3D+2D)
- Back Light Compensation (Area Setting)
- Advanced Motion Detection Function
- eXtended Dynamic Range (XDR)
- Privacy Mask Function (Polygonal Mosaic)
- DIS (Digital Image Stabilization)
- CCVC (Camera Control Via Coaxial cable, Controller : SCX-RD100)
- Multi-Language OSD support
- Intelligent Video (Moved / Fixed / Fence / Area / Tracking)
- Anti Vandal type, IP-66, Surface type
- DC12V & AC24V 60Hz(50Hz)
- Applicable Wall mount adaptor : SADT-102WM

Specifications

Model	SCC-B5396N/B5398N	SCC-B5396P/B5398P	
Camera Type	Color/BW		
Image	Color		
Image	Device	1/3" Super-HAD IT CCD	
	Pixels	Effective	
	768 x 494	752 x 582	
Scanning	System		
	Interlace		
	Horizontal	Internal Mode	15,734 Hz
		Line-lock Mode	15,750 Hz
Frequency	Internal Mode	59.94 Hz	
	Line-lock Mode	60 Hz	
Resolution	Horizontal	600 TV Lines	
Min. Scene Illumination	Sens-up off	0.12Lux(15 IRE), 0.2Lux(30 IRE), 0.4Lux(50 IRE)@F1.2	
	Sens-up	0.00023Lux(15 IRE), 0.0005Lux(30 IRE), 0.0008Lux(50 IRE)@F1.2	
Functions	Number of Privacy Zone		
	12 (Polygonal Method)		
	Day/Night		
	Color/BW/AUTO(Soft)		
	Motion Detection		
	Off/On		
	D-Zoom		
	1x ~16x (0.1x STEP)		
	High Speed Shutter		
	1/60 ~ 1/10Ksec (OSD) / 1/50 ~ 1/10Ksec (OSD)		
	Sens Up / BLC / AGC		
	2x ~ 512x / Off/On / Off/On		
	Line Lock / Anti Vandal		
	Off/On (Phase Control) / Yes		
Camera ID / White Balance			
Off/On (Max.54ea/2Lines) / ATW1/ATW2/AWC/MANUAL			
eXtended Dynamic Range			
Off/Low/Mid/High			
Digital Noise Reduction			
Off/On			
Digital Image Stabilization			
Off/On			
Intelligent Video			
Off/On(Moved / Fixed / Fence / Area / Tracking)			
PIP			
Off/On			
Etc. Function			
Detail, Reverse(H/V), Posi/Nega			
Video Output	VBS 1.0Vp-p	VBS 1.0VpN/Ap	
S/N Ratio	52 dB		
Lens	Focal Length		
	SCC-B5396 : 2.5~6mm / SCC-B5398 : 2.8~11mm		
	Zoom ratio		
	SCC-B5396 : 2.4x / SCC-B5398 : 3.4x		
	Aperature Ratio		
	F1.2		
Viewing Angle	Tele	SCC-B5396:46°(H) x 34°(V) / SCC-B5398:28.8°(H) x 21.6°(V)	
	Wide	SCC-B5396:108°(H) x 80°(V) / SCC-B5398:94.6°(H) x 68.4°(V)	
Lens Drive Type / Mount Type		AI(DC) / Board Type	
OSD	Yes		
Remote Control	CCVC	Yes (with SCX-RD100)	
	RS485	Yes (Multi Protocol, 8ea)	
Environmental Conditions	Operating Temperature	Absolute : -10°C ~ +50°C / Sustained : -20°C ~ +60°C	
	Operating Humidity	Less than 90%	
Power	Power Requirement	24 VAC ±10%/12 VDC ±10%	
Physical Specification	Dimensions		
	150(φ) x 121(H) mm		
	Weight		
	1,000g		
	Color	Body	
	White	White	

Dimensions (unit:mm)

